Abstract

Smart Home is a combination of information technology and computing

technologies applied in homes or buildings inhabited by humans by relying on

efficiency, automation devices, comfort, safety, and savings of home electronic devices.

In accordance with technological developments, the current production of smart home

has been much developed with various concepts and systems in the wake. Smart home

can be integrated with other production technologies that are currently being widely

used as integrating it with the Arduino Uno and the operating system is open source in

the Android mobile platform.

At this final project, it has designed a prototype of Smart Home system with

client-server-based user interface arduino uno with android that will perform data

communication via wireless (without cable). Construction stage begins with build a

server, build interfaces, as well as its smart home control system. On the server side will

use the programming languages C and C ++ while the user side using Java

programming language. On the server will use a method or protocol Common Gateway

Interface berfungi as a liaison between the android platform with modules used arduino

uno. Server and client will communicate via wireless after pensettingan IP so as to have

the same local network.

By using a system that has been adopted allows the Smart Home can be

accessed by multiclient. The results showed there is a delay that is influenced by

distance, type of room and obstacle. The average value of the lowest delay and delay is

0.061641 s high of 0.1242242 s. While the highest RSSI is worth -52 dBm and -86 dBm

weakest worth. Expected output for further study is to obtain an analysis that is able to

serve as a reference concept of Smart Home or home automation more efficient that can

be applied in real application.

Keyword: Smart Home, Common Gateway Interface, Android, Client-Server