

TABLE OF CONTENTS

TITLE PAGE	i
APPROVAL PAGE	i
SELF DECLARATION AGAINTS PLAGIARISM	ii
ABSTRACT	iii
PREFACE	iv
DEDICATION	v
TABLE OF CONTENTS	vi
LIST OF TABLES	x
LIST OF FIGURES	xii
LIST OF GLOSARY	xiii
APPENDIX LIST	xiv
CHAPTER 1. INTRODUCTION	1
1.1. Background	1
1.2. Problem	4
1.3. Objective	4
1.4. Hypothesis	4
1.5. Research Method	4
CHAPTER 2. SATELLITE COMMUNICATION SYSTEM	7
2.1. Channel Coding to Resolve Rain Fading Channel at Tropical Area	8
2.2. Adaptive Modulation and Coding with SNR Estimator and Punctured Convolutional Coding for Spectral and Quality Improvement for the Wireless Channel	9
2.3. Various Combining Techniques and Adaptive Coded Modulation	10
2.4. Clear Sky Uplink Performance	10
2.4.1. Antenna Gain	11
2.4.2. Radiation Pattern and Angular Beamwidth	11
2.4.3. <i>Effective Isotropic Radiated Power (EIRP)</i>	12
2.4.4. Attenuation in The Atmosphere	12
2.4.5. Losses in The transmitting and Receiving Equipment	12
2.4.6. Depointing Losses	13
2.4.7. Figure of Merit G/T of the satellite (SL)	13
2.5. Clear Sky Downlink Performance	13

2.6. Channel Coding and The Power-Bandwidth Trade-Off	14
2.6.1. Coding with variable bandwidth	14
2.6.2. Coding with constant bandwidth	16
2.7. Rain Attenuation	17
2.8. Mitigation of Atmospheric Mitigation	20
2.8.1. Attenuation Mitigation	20
2.8.2. Site diversity	20
2.8.2.1. Diversity gain $G_D(p)$	20
2.8.2.2. Diversity Improvement Factor F_D	21
2.8.3. Adaptivity	21
2.8.4. Cost–Availability Trade-Off	21
2.9. Link Performance Comparisson between Multibeam and Monobeam Coverage	22
 CHAPTER 3. FORMULATION AND MODELLING PROPOSED ADAPTIVE CODING AND MODULATION	27
3.1. The Data Collection	26
3.1.1. HTS Ka-band Technical Specification	27
3.1.2. HTS Ground System Configuration in Indonesia	28
3.1.3. Rain Rate of 30 cities in Indonesia	28
3.1.4. Coding and Modulation Parameters	29
3.2. The Data Processing : Link Budget Simulation	29
3.2.1. Effective Isotropic Radiated Power (EIRP)	29
3.2.2. Antenna Gain	30
3.2.3. Figure of Merit (G/T)	30
3.2.4. Free Space Loss	30
3.2.5. Transmitter and Receiver Line Loss	31
3.2.6. Atmosphere Loss	31
3.2.7. Rain Attenuation	31
3.2.8. Carrier to Noise Ratio	33
3.3. The Link Budget Scenario	36
 CHAPTER 4. PRESENTATION, ANALYSIS AND INTERPRETATION OF DATA	45
4.1. Link Budget for Worst Condition	45
4.1.1. The C/N_{uplink} Calculation	46
4.1.2. The $C/N_{downlink}$ Calculation	47

4.1.3. The C/N _{TOTAL} Calculation	48
4.2. Threshold Determination to Trigger ModCod Adaptation for Worst Condition	43
4.2.1. Result For Clear Sky Condition in both Medan and Padang	43
4.2.2. Result For Minimum Rain (5.4 mm/hr) in Medan and Clear Sky in Padang	44
4.2.3. Result For Average Rain (31 mm/hr) in Medan and Clear Sky in Padang	45
4.2.4. Result For Maximum Rain (64 mm/hr) in Medan and Clear Sky in Padang	46
4.2.5. Result For Clear Sky in Medan and Minimum Rain (28.6 mm/hr) in Padang	47
4.2.6. Result For Clear Sky in Medan and Average Rain (57 mm/hr) in Padang	48
4.2.7. Result For Minimum Rain Rate 5.4 mm/hr in both Medan and Padang	49
4.2.8. Result For Rain Rate 28.6 mm/hr in both Medan and Padang	50
4.3. Link Budget for Gateway and End-user terminal for Average Condition	52
4.3.1. The C/N _{uplink} Calculation	52
4.3.2. The C/N _{downlink} Calculation	53
4.3.3. The C/N _{TOTAL} Calculation	54
4.4. Threshold Determination to Trigger ModCod Adaptation for Average Condition	56
4.4.1. Result For Clear Sky Condition in both Makasar and Sorong	57
4.4.2. Result For Minimum Rain (0.4 mm/hr) in Makasar and Clear Sky in Sorong	58
4.4.3. Result For Average Rain (37 mm hr) in Makasar and Clear Sky in Sorong	59
4.4.4. Result For Maximum Rain (151 mm hr) in Makasar and Clear Sky in Sorong	60
4.4.5. Result For Clear Sky in Makasar and Minimum Rain (5.6 mm hr) in Sorong	61
4.4.6. Result For Clear Sky in Makasar and Average Rain (44 mm hr) in Sorong	62
4.4.7. Result For Clear Sky in Makasar and Average Rain (228 mm hr) in Sorong	63
4.4.8. Result For Minimum Rain Rate 5.6 mm hr in both Makasar and Sorong	64
4.4.9. Result For Rain Rate 37 mm hr in both Makasar and Sorong	65
4.5. Link Budget Calculation of Gateway and End-user terminal for Favorable Condition	66
4.5.1. The C/N _{uplink} Calculation	67
4.5.2. The C/N _{downlink} Calculation	68
4.5.3. The C/N _{TOTAL} Calculation	69
4.6. Threshold Determination to Trigger ModCod Adaptation for Favorable Condition	71
4.6.1. Result For Clear Sky Condition in both Denpasar and Mataram	72
4.6.2. Result For Average Rain (20 mm hr) in Denpasar and Clear Sky in Mataram	74
4.6.3. Result For Maximum Rain (102 mm hr) in Denpasar and Clear Sky in Mataram	75
4.6.4. Result For Clear Sky in Denpasar and Minimum Rain (0.01 mm hr) in Mataram	76

4.6.5. Result For Clear Sky in Denpasar and Average Rain (17 mm/hr) in Mataram	77
4.6.6. Result For Clear Sky in Denpasar and Average Rain (109 mm/hr) in Mataram	78
4.6.7. Result For Minimum Rain Rate 0.5 mm/hr in both Denpasar and Mataram	79
4.6.8. Result For Rain Rate 20 mm/hr in both Denpasar and Mataram	80

CHAPTER 5. CONCLUSION AND RECOMMENDATION

5. 1. Conclusions	98
5. 2. Recommendations / Future Work	99

REFERENCES	xv
------------	----

APPENDICES	xvii
------------	------