

DAFTAR PUSTAKA

- [1] Z. Wenjing, Z. Tiedong, W. Le, and Q. Zaibai, “An improved association method of SLAM based on ant colony algorithm,” *2009 4th IEEE Conf. Ind. Electron. Appl. ICIEA 2009*, pp. 1545–1548, 2009.
- [2] S. H. Joo, U. H. Lee, T. Y. Kuc, and J. K. Park, “A robust SLAM algorithm using hybrid map approach,” *Int. Conf. Electron. Inf. Commun. ICEIC 2018*, vol. 2018-January, no. 7, pp. 1–2, 2018.
- [3] P. Benavidez, M. K. Muppidi, and M. Jamshidi, “Improving visual SLAM algorithms for use in realtime robotic applications,” pp. 1–6, 2015.
- [4] Y.-J. Shih, C.-C. Hsu, W.-Y. Wang, and Y.-T. Wang, “Feature extracted algorithm for simultaneous localization and mapping (SLAM),” pp. 497–498, 2015.
- [5] F. Wen, X. Chai, Y. Li, W. Zou, K. Yuan, and P. Chen, “An improved visual SLAM algorithm based on mixed data association,” *Proc. World Congr. Intell. Control Autom.*, pp. 1081–1086, 2011.
- [6] H. A. Kadir and M. R. Arshad, “Improved simultaneous localization and mapping (SLAM) algorithms for aerial vehicle under dynamic sea surface environment,” *USYS 2016 - 2016 IEEE 6th Int. Conf. Underw. Syst. Technol. Theory Appl.*, pp. 61–66, 2017.
- [7] J. Alexandersson, “Implementation of SLAM algorithms in a small-scale vehicle using model-based development,” 2017.
- [8] J. Griffin, “DC motors,” *Electron. Power*, vol. 28, no. 1, p. 109, 2010.
- [9] W. Chen, T. Qu, Y. Zhou, K. Weng, G. Wang, and G. Fu, “Door recognition and deep learning algorithm for visual based robot navigation,” *2014 IEEE Int. Conf. Robot. Biomimetics, IEEE ROBIO 2014*, pp. 1793–1798, 2014.
- [10] F. Liu, S. Liang, and X. Xian, “Multi-robot task allocation based on utility and distributed computing and centralized determination,” *Proc. 2015 27th Chinese Control Decis. Conf. CCDC 2015*, pp. 3259–3264, 2015.
- [11] H. He, Y. Jia, and L. Sun, “Simultaneous Location and Map Construction Based on RBPF-SLAM Algorithm,” *Proc. 30th Chinese Control Decis. Conf. CCDC 2018*, pp. 4907–4910, 2018.

- [12] M. G. Ocando and N. Certad, “Autonomous 3D mapping of an enviroment , while simultaneously making 2D SLAM , using a single 2D LIDAR and ROS *,” pp. 2–7, 2017.
- [13] K. Takaya, T. Asai, V. Kroumov, and F. Smarandache, “Simulation environment for mobile robots testing using ROS and Gazebo,” *2016 20th Int. Conf. Syst. Theory, Control Comput. ICSTCC 2016 - Jt. Conf. SINTES 20, SACCS 16, SIMSIS 20 - Proc.*, pp. 96–101, 2016.
- [14] S. Y. Park and G. H. Lee, “Mapping and localization of cooperative robots by ROS and SLAM in unknown working area,” *2017 56th Annu. Conf. Soc. Instrum. Control Eng. Japan, SICE 2017*, vol. 2017-November, pp. 858–861, 2017.
- [15] L. SHANGHAI SLAMTEC CO., “Rplidar a1,” pp. 1–16, 2009.
- [16] T. C. Authors, “Cartographer Documentation,” 2018.
- [17] B. D. Teori, “Kendali motor dc,” no. I, pp. 2–7.
- [18] KPM, “Buku Panduan Pemrograman Python,” *Buku*, vol. 84, pp. 487–492, 2013.
- [19] E. Upton, “Raspberry Pi 3 Model B,
url:<https://www.raspberrypi.org/blog/raspberry-pi-3-model-bplus-sale-now-35/>,” p. 2837, 2018.
- [20] “User Manual of 3A UBEC 3 Amp Switch-Mode UBEC HW-SM810DUL-20130412,” p. 3.
- [21] J. Perry *et al.*, “L298 H Bridge,” *STMicroelectronics*, vol. 22, p. 1, 2000.
- [22] B. Heinold, “A Practical Introduction to Python Programming,” p. 263, 2012.