

## DAFTAR PUSTAKA

- [1] Jha, R., & Guha, P. K. (2017). An effective liquid-phase exfoliation approach to fabricate tungsten disulfide into ultrathin two-dimensional semiconducting nanosheets. *Springer*, 1-13.
- [2] Wang, Q. H., et al. (2012). Electronics and Optoelectronics of two-dimensional Transition Metal Dichalcogenides. *Nature Nanotechnology*, 699-712.
- [3] Ovchinnikov, D., et al. (2014). Electrical Transport Properties of Single-Layer WS<sub>2</sub>. *ACS NANO*, 1-8.
- [4] Helms, C. R., Deal, B. E. (1988) Eds. The Physics and Chemistry of SiO<sub>2</sub> and the Si-SiO<sub>2</sub> interface. *Plenum Press*: New York.
- [5] K.A. Sierros, N.J. Morris, S.N. Kukureka, D.R. Cairns. (2008). Dry and wet sliding wear of ITO-coated PET components used in flexible optoelectronic applications. *Elsevier*, 625-631.
- [6] Manzeli, S., et al. (2017). 2D transition metal dichalcogenides. *Nature Reviews*, 1-15.
- [7] Jo, S., et al. (2015). Electrostatically Induced Superconductivity at the Surface of WS<sub>2</sub>. *Nano Letters*, 1-6.
- [8] I. Kaplan-Ashiri, et al. (2004). Mechanical Behavior of Individual WS<sub>2</sub>Nanotubes. *J.Mater.Res.*, 454-459.
- [9] Bertolazzi, S., Brivio, J. & Kis, A. (2011). Stretching and breaking of ultrathin MoS<sub>2</sub>. *ACS Nano* **5**, 9703–9709.
- [10] Andrew, R., et al. (2012). Mechanical properties of graphene and boronitrene. *Phys. Rev. B* **85**, 125428.
- [11] Thanasis Georgiou, et al. (2012). Vertical Field Effect Transistor based on Graphene-WS<sub>2</sub> Heterostructure for flexible and transparent electronics, 1-13.

- [12] R. Tenne, L. Margulis, M. Genut & G. Hodes. (1992). Polyhedral and cylindrical structures of tungsten disulphide. *Nature* 360, 444-446.
- [13] P. A. Chate, D. J. Sathe, P. P. Hankare. (2012). Electrical, optical and morphological properties of chemically deposited nanostructured tungsten disulfide thin films. *Springer*, 19-23.
- [14] Heaney, Michael B. (2003). Electrical Conductivity and Resistivity. Electrical Measurement, Signal Processing, and Displays. Ed. John G. Webster. *CRC Press*, 7-1.
- [15] American Elements, Silicon Wafer,  
<https://www.americanelements.com/silicon-wafer-7440-21-3> , (diakses tanggal 1 November 2018).
- [16] R. K. Al-tamimi, M. N. Khalaf, M. Sabri, and L. Sabri. (2011). Post consumer poly(ethylene terephthalate) depolymerization by waste of battery acid hydrolysis. *J. Mater. Environ. Sci.*, 88–93.
- [17] Phoenix Technology International LLC., *Polyethylene Terephthalate Key Properties*,  
<http://www.phoenixtechnologies.net/media/371/PET%20Properties%202008.pdf>, (diakses tanggal 29 Oktober 2018).
- [18] Darran R. Cairns, et al. (2000). Strain-dependent electrical resistance of tin-doped indium oxide on polymer substrates. *Applied Physics Letters*, vol 76, Number 11, 1425-1427.
- [19] Do-Hyoung Kim, Han-Ki Yoon, Do-Hoon Shin, Ri-ichi Murakami. (2005). Mechanical properties of ITO/PET Thin Film Deposited by DC MG Method, IEEE, 174-178.
- [20] Material Property Database, *Material: Indium Tin Oxide (ITO)*,  
<http://www.mit.edu/~6.777/matprops/ito.htm> , (diakses tanggal 8 November 2018).

- [21] American Elements, *Indium Tin Oxide Coated PET*,  
<https://www.americanelements.com/indium-tin-oxide-coated-pet-50926-11-9>, (diakses tanggal 8 November 2018)
- [22] N.--pyrrolidinone Msds. (2013). Material Safety Data Sheet N-methyl-2-pyrrolidone. *Sci. Lab.com*, 1–6.
- [23] Mao et al. (2013). Ferromagnetism in exfoliated tungsten disulfide nanosheets. *Nanoscale Research Letters*, 1-6.
- [24] Cost Effective Equipment, Spin Coat Theory,  
<http://www.utdallas.edu/~rar011300/CEEspinner/SpinTheory.pdf> ,  
(diakses tanggal 31 Oktober 2018)
- [25] Ossila, Spin Coating: A Guide to Theory and Techniques,  
<https://www.ossila.com/pages/spin-coating>, (diakses tanggal 1 November 2018).
- [26] Jung et al. (2018). Measuring the optical permittivity of two-dimensional materials without a priori knowledge of electronic transitions. *Nanophotonics*, 263-270.
- [27] David B. Hall, Patrick Underhill, and John M. Torkelson. (1998). Spin Coating of Thin and Ultrathin Polymer Films. *Polymer Engineering and Science*, Vol. 38, No. 12.
- [28] Mishra, A. K. et al. (2015). Eco-friendly synthesis of metal dichalcogenides nanosheets and their environmental remediation potential driven by visible light. *Scientific Reports*, 1-8.
- [29] Sujatno et al. (2015). Studi Scanning Electron Microscopy (SEM) Untuk Karakterisasi Proses Oxidasi Paduan Zirkonium. *Jurnal Forum Nuklir (JFN)*, 44-50.
- [30] Mao et al. (2014). WS<sub>2</sub> mode-locked ultrafast fiber laser. *Scientific Reports*, 1-7.
- [31] Chemistry, LibreText: Van der Waals Interactions,  
[https://chem.libretexts.org/Bookshelves/Physical\\_and\\_Theoretical\\_Chemistry\\_Textbook\\_Maps/Supplemental\\_Modules\\_\(Physical\\_and\\_Theoretical\\_Chemistry\)/Physical\\_Properties\\_of\\_Matter/Atomic\\_and\\_Molecular\\_Properties/Intermolecular\\_Forces/Specific\\_Interactions/Van\\_Der\\_Waals\\_Interactions](https://chem.libretexts.org/Bookshelves/Physical_and_Theoretical_Chemistry_Textbook_Maps/Supplemental_Modules_(Physical_and_Theoretical_Chemistry)/Physical_Properties_of_Matter/Atomic_and_Molecular_Properties/Intermolecular_Forces/Specific_Interactions/Van_Der_Waals_Interactions) , (diakses tanggal 15 Juli 2019).

