## DAFTAR PUSTAKA


Akao, Y. (1990) *QFD: Quality Function Deployment - Integrating Customer Requirements into Product Design, Productivity Press*. doi: 9781563273131.

Chan, L. K. and Wu, M. L. (2005) 'A systematic approach to quality function deployment with a full illustrative example', *Omega*. doi: 10.1016/j.omega.2004.03.010.

Cooper, T. *et al.* (1994) 'BEYOND The longer life option The longer life option', (November).

Dağdeviren, M., Yavuz, S. and Kilinç, N. (2009) 'Weapon selection using the AHP and TOPSIS methods under fuzzy environment', *Expert Systems with Applications*, 36(4), pp. 8143–8151. doi: 10.1016/j.eswa.2008.10.016.

Davoodi, M. M. *et al.* (2011) 'Concept selection of car bumper beam with developed hybrid bio-composite material', *Materials and Design*. doi: 10.1016/j.matdes.2011.06.011.

Ertuğrul, İ. and Karakaşoğlu, N. (2009) 'Performance evaluation of Turkish cement firms with fuzzy analytic hierarchy process and TOPSIS methods', *Expert Systems with Applications*, 36(1), pp. 702–715. doi: 10.1016/j.eswa.2007.10.014.

Gudmundsson, A. (2009) 'Safety practices related to small fishing vessel stability', pp. 1–64.

Hwang, C. and Yoon, K. (1981) *Multiple Attribute Decision Making: Methods and Applications, A State of the Art Survey, Springer-Verlag*. doi: 10.1007/978-3-642-48318-9.

Ii, B. A. B. (2016) '2016 2.1', pp. 4–35.

Majumdar, A., Kaplan, S. and Göktepe, Ö. (2010) 'Navel selection for rotor spinning denim fabrics using a multi-criteria decision-making process', *Journal of the Textile Institute*. doi: 10.1080/00405000802399619.

Munde, K. and Wagh, M. N. (2018) 'Design And Analysis Of River Water Skimmer', *International Journal of Recent Trends in Engineering and Research*, 4(7), pp. 126–132. doi: 10.23883/IJRTER.2018.4365.EU0JS.

Partovi, F. (1994) 'Determining what to benchmark: an analytic hierarchy process approach', *International Journal of Operations & Production Management*. doi: 10.1016/j.jchromb.2008.10.004.

Partovi, F. Y. (1994) ‘Determining What to Benchmark: An Analytic Hierarchy Process Approach’, *International Journal of Operations & Production Management*, 14(6), pp. 25–39. doi: 10.1108/01443579410062068.

Pérez, F. *et al.* (2008) ‘Parametric Generation , Modeling, and Fairing of Simple Hull Lines With the Use of Nonuniform Rational B-Spline Surfaces’, *Journal of Ship Research*, 52(1), pp. 1–15.

Rao, R. V. and Davim, J. P. (2008) ‘A decision-making framework model for material selection using a combined multiple attribute decision-making method’, *International Journal of Advanced Manufacturing Technology*, 35(7–8), pp. 751–760. doi: 10.1007/s00170-006-0752-7.

Shanian, A. and Savadogo, O. (2006) ‘ELECTRE I decision support model for material selection of bipolar plates for polymer electrolyte fuel cells applications’, *Journal of New Materials for Electrochemical Systems*. doi: 10.1016/j.jpowsour.2005.12.092.

Wibowo, P. A. (2013) ‘Analisis penurunan head losses pada belokan pipa 180’.

Yang, T. and Chou, P. (2005) ‘Solving a multiresponse simulation-optimization problem with discrete variables using a multiple-attribute decision-making method’, *Mathematics and Computers in Simulation*. doi: 10.1016/j.matcom.2004.09.004.

Yoon, K. P. and Hwang, C.-L. (1995) *Multiple attribute decision making: An introduction., Multiple attribute decision making: An introduction.* doi: http://dx.doi.org/10.4135/9781412985161.