

## LIST OF FIGURES

2.1	WBAN Configuration . . . . .	5
2.2	PIFA Antenna. . . . .	6
2.3	The Reactively-loaded Antenna Method. . . . .	9
3.1	Antenna System Block Diagram. . . . .	12
3.2	Design of PIFA. . . . .	13
3.3	Patch Antenna Dimension. . . . .	15
3.4	Adjusting Width and Length of Patch Dimension. . . . .	16
3.5	Return Loss of First Resonance Frequency. . . . .	17
3.6	Dual Frequency Return Loss. . . . .	17
3.7	Return Loss of Second Resonance Frequency. . . . .	18
3.8	Patch Dimension with L-shaped Slot. . . . .	19
3.9	L-shaped Slot Optimization. . . . .	19
3.10	Short Pin Optimization. . . . .	20
3.11	Height of Antenna Optimization. . . . .	21
3.12	Slot on The Ground Plane. . . . .	22
3.13	Width Slot of Ground Plane Optimization. . . . .	22
3.14	Final Result of Patch Design. . . . .	23
3.15	Final Result of Ground Plane Design. . . . .	24
3.16	Return Loss's Graph Simulation Result. . . . .	24
3.17	Bandwidth for 900 MHz Frequency. . . . .	25
3.18	Bandwidth for 2.4 GHz Frequency. . . . .	25
3.19	VSWR of First Resonance Frequency . . . . .	26
3.20	VSWR of Second Resonance Frequency . . . . .	26
4.1	PIFA Antenna Fabrication. . . . .	27
4.2	Vector Network Analyzer (VNA). . . . .	28
4.3	Return Loss Measurement. . . . .	28
4.4	Return Loss Measurement with Microsoft Excel. . . . .	29
4.5	Comparison Return Loss Results Between Simulation and Mea- surement. . . . .	29
4.6	VSWR Measurement with Microsoft Excel. . . . .	30
4.7	VSWR Measurement. . . . .	30

4.8 Comparison VSWR Results Between Simulation and Measurement. 31