

## DAFTAR ISTILAH

LTE	= <i>Long Term Evolution</i>
3GPP	= <i>Third Generation Partnership Project</i>
MAPL	= <i>Maximum Allowable Path Loss</i>
MaxTP	= <i>Max Transmit Power (dBm)</i>
SP	= <i>Subcarrier Power</i>
AG	= <i>Antenna Gain (dBi)</i>
$3dB Sp_{Loss}$	= <i>3dB Hybrid Coupler 1/2 Way Splitter Loss (dB)</i>
$\frac{1}{2} Cab_{Loss}$	= <i>1/2 " Cable Loss (dB)</i>
$PI_{PA}$	= <i>Power Input for Panel Antenna</i>
$T_{Loss}$	= <i>Train Loss (dB)</i>
$B_{Loss}$	= <i>Body Loss (dB)</i>
EngM	= <i>Engineering Margin (dB)</i>
MinSL	= <i>Minimum Signal Level Requirement (dBm)</i>
$L_T$	= <i>Link budget total (MAPL)</i>
$L_{FSL}$	= <i>Free Space Loss antara transmitter dan receiver</i>
$L_C$	= <i>Constant Loss (37 dB)</i>
$w$	= <i>Jumlah tipe dinding</i>
$n_{wi}$	= <i>Jumlah dinding yang dilewati sinyal</i>
$L_{wi}$	= <i>Nilai loss pada dinding</i>
$L_f$	= <i>Loss pada lantai (18,3 dB)</i>
$n_f$	= <i>Jumlah lantai yang dilewati sinyal</i>
$b$	= <i>Empirical parameter</i>
$d_{km}$	= <i>Cell radius dalam kilometer</i>
eNode B	= <i>Evolved Node B, penamaan base station pada teknologi 4G</i>

