

DAFTAR REFERENSI

- [1] M. R. Hartono and H. Subawi, *Pengenalan teknik komposit*. Deepublish, 2016.
- [2] D. A. Vajari, C. Gonzalez, J. Llorca, and B. N. Legarth, “A numerical study of the influence of microvoids in the transverse mechanical response of unidirectional composites,” *Composites Science and Technology*, vol. 97, pp. 46–54, 2014.
- [3] M. Mehdikhani, L. Gorbatiikh, I. Verpoest, and S. V. Lomov, “Voids in fiber-reinforced polymer composites: A review on their formation, characteristics, and effects on mechanical performance,” *Journal of Composite Materials*, vol. 53, no. 12, pp. 1579–1669, 2019.
- [4] L. Maragoni, P. Carraro, M. Peron, and M. Quaresimin, “Fatigue behaviour of glass/epoxy laminates in the presence of voids,” *International Journal of Fatigue*, vol. 95, 10 2016.
- [5] A. Rale, D. Gharpure, and V. Ravindran, “Comparison of different techniques for automatic defect detection in x-ray images,” 12 2009, pp. 193–197.
- [6] N. N. Septina, I. P. Handayani, and H. B. Dyah K., “Identifikasi efek keseragaman terhadap penyebaran resin pada bahan fiber dengan metoda multilevel threshold,” *Jurnal Telkom University*, vol. 8, no. 2, 2019.
- [7] M. Mehdikhani, N. Petrov, I. Straumit, A. R. Melro, S. Lomov, and L. Gorbatiikh, “The effect of voids on matrix cracking in composite laminates as revealed by combined computations at the micro- and meso-scales,” *Composites Part A: Applied Science and Manufacturing*, vol. 117, 11 2018.
- [8] A. Jatmiko and S. Hadi, “Alat wet lay up terkontrol sederhana dan analisis pengaruh proses lay up terhadap sifat mekanik material komposit,” *Jurnal Telkom University*, vol. 4, no. 1, pp. 803–810, 2017.
- [9] P. N. Andono, T. Sutojo, and Muljono, *Pengolahan Citra Digital*. Penerbit Andi, 2017.
- [10] Mathwork Help Center. rgb2gray. [Online]. Available: <https://www.mathworks.com/help/matlab/ref/rgb2gray.html>

- [11] Y.-J. Zhang, *Advances in image and video segmentation*. IGI Global, 2006.
- [12] F. Wang, L.-Y. Hou, and H. Huang, “Degraded chinese rubbing images thresholding based on local first-order statistics,” in *Second International Workshop on Pattern Recognition*, vol. 10443. International Society for Optics and Photonics, 2017, p. 1044307.
- [13] C. Santulli, R. Gil, A. Long, and M. Clifford, “Void content measurements in commingled e-glass/ polypropylene composites using image analysis from optical micrographs,” *Science and Engineering of Composite Materials*, vol. 10, 01 2002.
- [14] S. Paciornik and J. D’Almeida, “Measurement of void content and distribution in composite materials through digital microscopy,” *Journal of Composite Materials*, vol. 43, no. 2, pp. 101–112, 2009. [Online]. Available: <https://doi.org/10.1177/0021998308098234>
- [15] C. Dingding, K. Arakawa, and C. Xu, “Reduction of void content of vacuum-assisted resin transfer molded composites by infusion pressure control,” *Polymer Composites*, vol. 36, 05 2014.
- [16] A. K. Chaubey, “Comparison of the local and global thresholding methods in image segmentation,” *World Journal of Research and Review*, vol. 2, no. 1, 1 2016.
- [17] D. Bradley and G. Roth, “Adaptive thresholding using the integral image,” *J. Graphics Tools*, vol. 12, pp. 13–21, 01 2007.
- [18] K. Pałka, J. Jakubowicz, G. Adamek, and A. G., “Micro-ct analysis and mechanical properties of ti spherical and polyhedral void composites made with saccharose as a space holder material,” *Materials Characterization*, vol. 100, pp. 13–20, 02 2015.
- [19] C. Du, S. Jiang, W. Qin, and Y. Zhang, “Numerical analysis of concrete composites at the mesoscale based on 3d reconstruction technology of x-ray ct images,” *CMES - Computer Modeling in Engineering and Sciences*, vol. 81, pp. 229–247, 11 2011.
- [20] A. Madra, N. EL Hajj, and M. Benzeggagh, “X-ray microtomography applications for quantitative and qualitative analysis of porosity in woven glass fiber reinforced thermoplastic,” *Composites Science and Technology*, 02 2014.

- [21] A. Bovik, “Handbook of image & video processing,” January 2010.
- [22] P. Soroushian and M. Elzafraney, “Morphological operations, planar mathematical formulations, and stereological interpretations for automated image analysis of concrete microstructure,” *Cement and Concrete Composites*, vol. 27, no. 7-8, pp. 823–833, 2005.
- [23] Mathwork Help Center. Structuring elements. [Online]. Available: <https://www.mathworks.com/help/images/structuring-elements.html>
- [24] R. Brunelli, *Template matching techniques in computer vision: theory and practice*. John Wiley & Sons, 2009.
- [25] M. W. Czabaj, M. L. Riccio, and W. W. Whitacre, “Numerical reconstruction of graphite/epoxy composite microstructure based on sub-micron resolution x-ray computed tomography,” *Composites Science and Technology*, vol. 105, pp. 174–182, 2014.
- [26] J. P. Lewis, “Fast template matching,” *Vision Interface 95*, pp. 120–123, 1995.
- [27] J. Lewis, “Fast normalized cross-correlation,” *Vision Interface 95*, 1995.
- [28] H. Zhu, B. Wu, D. Li, D. Zhang, and Y. Chen, “Influence of voids on the tensile performance of carbon/epoxy fabric laminates,” *Journal of Materials Science & Technology*, vol. 27, no. 1, pp. 69–73, 2011.
- [29] Fourjay. Black circle.png. [Online]. Available: <https://www.fourjay.org/pl/11612>
- [30] B. S. Hayes and L. M. Gammon, *Optical microscopy of fiber-reinforced composites*. ASM international, 2010.