

DAFTAR PUSTAKA

- [1] C. R. Gould, C. M. Bingham, D. A. Stone, and P. Bentley, “New battery model and state-of-health determination through subspace parameter estimation and state-observer techniques,” *IEEE Trans. Veh. Technol.*, vol. 58, no. 8, pp. 3905–3916, 2009, doi: 10.1109/TVT.2009.2028348.
- [2] M. Thowil Afif and I. Ayu Putri Pratiwi, “Analisis Perbandingan Baterai Lithium-Ion, Lithium-Polymer, Lead Acid dan Nickel-Metal Hydride pada Penggunaan Mobil Listrik - Review,” *J. Rekayasa Mesin*, vol. 6, no. 2, pp. 95–99, 2015, doi: 10.21776/ub.jrm.2015.006.02.1.
- [3] S. Ramon, G. S. Brewer, and S. Ramon, “(12) Patent Application Publication (10) Pub . No . : US 2014 / 0368161 A1,” vol. 1, no. 19, 2014.
- [4] I. R. Tyesadha, R. F. Iskandar, and I. W. Fathonah, “ESTIMASI STATE OF CHARGE PADA BATERAI LITHIUM ION MENGGUNAKAN METODE SUPPORT VECTOR MACHINE (SVM) ESTIMATION STATE OF CHARGE ON LITHIUM ION BATTERY USING SUPPORT VECTOR MACHINE (SVM) METHOD,” vol. 5, no. 2, pp. 2322–2328, 2018.
- [5] E. S. Division, “A review of battery life-cycle analysis: State of knowledge and critical needs,” *Batter. Manuf. Electr. Hybrid Veh.*, pp. 91–133, 2011.
- [6] H. Out, K. Fisika, H. Out, and K. Fisika, “Arus listrik 1.,” no. dc, pp. 76–78, doi: 10.1063/1.2713206.
- [7] C. Zou, C. Manzie, D. Nešić, and A. G. Kallapur, “Multi-time-scale observer design for state-of-charge and state-of-health of a lithium-ion battery,” *J. Power Sources*, vol. 335, pp. 121–130, 2016, doi: 10.1016/j.jpowsour.2016.10.040.
- [8] M. J. Piernas Muñoz and E. Castillo Martínez, “Introduction to batteries,”

- SpringerBriefs Appl. Sci. Technol.*, no. December, pp. 1–8, 2018, doi: 10.1007/978-3-319-91488-6_1.
- [9] A. Bayu, D. Darmawan, A. Qurthobi, F. T. Elektro, and U. Telkom, “Perancangan Dan Implementasi Alat Ukur State of Charge Sistem Pengawasan Pada Baterai Lead Acid Menggunakan Metode Open Circuit Voltage,” vol. 4, no. 1, pp. 752–760, 2017.
- [10] J. Heri and S. T. Mt, “PENGUJIAN SISTEM PEMBANGKIT LISTRIK TENAGA SURYA SOLAR CELL KAPASITAS 50WP,” pp. 47–55, 1954.
- [11] A. D. Isnaini, R. F. Iskandar, F. T. Elektro, U. Telkom, and P. Coulomb, “Estimasi State of Charge Pada Baterai Lithium Ion menggunakan Metode Perhitungan Coulomb Estimation State of Charge of Lithium Ion Battery Using Coulomb,” vol. 4, no. 1, pp. 650–657, 2017.
- [12] B. Sumantri, A. Abimayu, and N. Tamami, “Sistem Portable Dashboard Berbasis Android untuk Mobil Listrik,” *J. Rekayasa Elektr.*, vol. 14, no. 3, 2018, doi: 10.17529/jre.v14i3.11826.
- [13] A. Fitriandi, E. Komalasari, and H. Gusmedi, “Rancang Bangun Alat Monitoring Arus dan Tegangan Berbasis Mikrokontroler dengan SMS Gateway,” *Rekayasa dan Teknol. Elektro*, vol. 10, no. 2, pp. 87–98, 2016, [Online]. Available: <http://electrician.unila.ac.id/index.php/ojs/article/download/215/pdf>.
- [14] I. H. Kurniawan and L. Hayat, “Perancangan Dan Implementasi Alat Ukur Tegangan, Arus Dan Frekuensi Listrik Arus Bolak-Balik Satu Fasa Berbasis Personal Computer,” *Techno*, vol. 15, no. 1, pp. 21–31, 2014.
- [15] J. McDowall, “Battery life considerations in energy storage applications and their effect on life cycle costing,” *Proc. IEEE Power Eng. Soc. Transm. Distrib. Conf.*, vol. 1, no. SUMMER, pp. 452–455, 2001, doi: 10.1109/pess.2001.970068.
- [16] K. Takahashi, “Physical Changes in Positive Active Mass during Deep Discharge-Charge Cycles of Lead-Acid Cell,” *J. Electrochem. Soc.*, vol. 130,

no. 11, p. 2144, 1983, doi: 10.1149/1.2119542.

- [17] S. Yata, Y. Hato, K. Sakurai, T. Osaki, K. Tanaka, and T. Yamabe, “Polymer battery employing polyacenic semiconductor,” *Synth. Met.*, vol. 18, no. 1–3, pp. 645–648, 1987, doi: 10.1016/0379-6779(87)90954-4.
- [18] N. El Ghossein, J. P. Salameh, N. Karami, M. El Hassan, and M. B. Najjar, “Survey on electrical modeling methods applied on different battery types,” *2015 3rd Int. Conf. Technol. Adv. Electr. Electron. Comput. Eng. TAEECE 2015*, pp. 39–44, 2015, doi: 10.1109/TAEECE.2015.7113597.