

DAFTAR GAMBAR

	Halaman
Gambar 2.1 Arsitektur jaringan LTE.....	8
Gambar 2.2 Arsitektur <i>relay node</i>	11
Gambar 2.3 <i>Transparent mode</i>	12
Gambar 2.4 <i>Non-Transparent mode</i>	12
Gambar 2.5 <i>Inband Relay Node</i>	13
Gambar 2.6 <i>Outband relay node</i>	14
Gambar 2.7 Skema <i>link budget uplink</i>	22
Gambar 2.8 Skema <i>link budget downlink</i>	24
Gambar 3. 1 Pemodelan <i>relay node</i>	28
Gambar 3. 2 Kondisi jalan tol Buah Batu – Pasteur Bandung	29
Gambar 3. 3 Luas dan letak jalan tol Buah Batu – Pasteur Bandung.....	30
Gambar 3. 4 Flow chart pengerjaan tugas akhir.....	31
Gambar 3. 5 Flow chart capacity planning.....	33
Gambar 3. 6 Flow chart coverage planning.....	34
Gambar 3. 7 Flow chart simulasi sistem menggunakan Atoll 3.2.2.....	35
Gambar 3. 8 Hasil drive test jalan tol Buah Batu – Pasteur Bandung.....	37
Gambar 3. 9 Histogram nilai RSRP hasil initial drive test.....	38
Gambar 3. 10 Histogram nilai SINR hasil initial drive test	38
Gambar 3. 11 <i>Relay node tipe 3</i>	50
Gambar 3. 12 Data site existing	51
Gambar 3. 13 Data transmitter existing.....	51
Gambar 3. 14 Data cell existing	52
Gambar 3. 15 eNodeB existing pada Atoll.....	52
Gambar 3. 16 Nilai rata-rata coverage by signal level dalam histogram	53
Gambar 3. 17 Nilai rata-rata coverage by C/(I+N) level dalam histogram	53
Gambar 3.18 Hasil simulasi user rejected sebelum penambahan <i>relay node</i>	54
Gambar 3.19 Data <i>relay node</i>	55
Gambar 3. 20 Peletakan <i>relay node</i> pada Atoll	55
Gambar 4. 1 Hasil prediksi <i>coverage by signal level</i> pada Atoll.....	56

Gambar 4. 2	Histogram hasil prediksi <i>coverage by signal level</i> pada <i>Atoll</i>	57
Gambar 4. 3	Hasil prediksi <i>coverage by C/(I+N) level</i> pada <i>Atoll</i>	58
Gambar 4. 4	Histogram hasil prediksi <i>coverage by C/(I+N) level</i> pada <i>Atoll</i>	58
Gambar 4. 5	Total <i>user</i> yang terhubung	59
Gambar 4. 6	Total <i>user rejected</i>	59
Gambar 4. 7	Perbandingan <i>RSRP before</i> dan <i>after</i> perancangan <i>relay node</i>	61
Gambar 4. 8	Perbandingan <i>SINR before</i> dan <i>after</i> perancangan <i>relay node</i>	61
Gambar 4. 9	<i>User rejected before after</i> perancangan <i>relay node</i>	62
Gambar 4. 10	Persentase akses layanan setelah perancangan <i>relay node</i>	63