References

[1] K. Srikulnath et al., "Overview of the betta fish genome regarding species radiation, parental care, behavioral aggression, and pigmentation model relevant to humans," *Genes Genomics,*, vol. 43, no. 2, pp. 91–104, 2021, doi: 10.1007/s13258-020-01027-2.

[2] B. Panijpan, N. Sriwattanarothai, and P. Laosinchai, "Wild Betta fighting fish species in Thailand and other Southeast Asian countries," *ScienceAsia*, vol. 46, no. 4, pp. 382–391, 2020, doi: 10.2306/scienceasia1513-1874.2020.064.

[3] N. Sharma, V. Jain, and A. Mishra, "An Analysis of Convolutional Neural Networks for Image Classification," in *Procedia Comput. Sci.*, vol. 132, no. Iccids, pp. 377–384, 2018, doi: 10.1016/j.procs.2018.05.198.

[4] B. S. Rekha, G. N. Srinivasan, S. K. Reddy, D. Kakwani, and N. Bhattad, "Fish Detection and Classification Using Convolutional Neural Networks," *Adv. Intell. Syst. Comput*, vol. 1108 AISC, no. January, pp. 1221–1231, 2020, doi: 10.1007/978-3-030-37218-7_128.

[5] D. Rathi, S. Jain, and S. Indu, "Underwater Fish Species Classification using Convolutional Neural Network and Deep Learning," in *2017 Ninth Int. Conf. Adv. Pattern Recognit.*, pp. 344–349, 2018, doi: 10.1109/ICAPR.2017.8593044.

[6] G. Ding, Y. Song, J. Guo, C. Feng, G. Li, and B. He, "Fish Recognition Using Convolutional Neural Network," *Ocean. 2017 - Anchorage*, pp. 0–3, 2017.

[7] L. Mookdarsanit and P. Mookdarsanit, "SiamFishNet: The Deep Investigation of Siamese Fighting Fishes," *Int. J. Appl. Comput. Technol. Inf. Syst.*, vol. 8, no. 2, pp. 40–46, 2019.

[8] Z. Chen, Z. Xie, W. Zhang, and X. Xu, "ResNet and model fusion for automatic spoofing detection," *Proc. Annu. Conf. Int. Speech Commun. Assoc. INTERSPEECH*, vol. 2017-Augus, pp. 102–106, 2017, doi: 10.21437/Interspeech.2017-1085.

[9] S. Vani and T. V. M. Rao, "An experimental approach towards the performance assessment of various optimizers on convolutional neural network," *Proc. Int. Conf. Trends Electron. Informatics, ICOEI 2019*, no. Icoei, pp. 331–336, 2019, doi: 10.1109/ICOEI.2019.8862686.

[10] R. Sachin, V. Sowmya, D. Govind, and K. P. Soman, "Dependency of various color and intensity planes on CNN based image classification," *Adv. Intell. Syst. Comput.*, vol. 678, pp. 167–177, 2018, doi: 10.1007/978-3-319-67934-1_15.

[11] R. L. Kumar, J. Kakarla, B. V. Isunuri, and M. Singh, "Multi-class brain tumor classification using residual network and global average pooling," *Multimed. Tools Appl.*, vol. 80, no. 9, pp. 13429–13438, 2021, doi: 10.1007/s11042-020-10335-4.

[12] M. Heidari, S. Mirniaharikandehei, A. Z. Khuzani, G. Danala, Y. Qiu, and B. Zheng, "Improving the performance of CNN to predict the likelihood of COVID-19 using chest X-ray images with preprocessing algorithms," *Int. J. Med. Inform.*, vol. 144, no. June, p. 104284, 2020, doi: 10.1016/j.ijmedinf.2020.104284.

[13] S. Sladojevic, M. Arsenovic, A. Anderla, D. Culibrk, and D. Stefanovic, "Deep Neural Networks Based Recognition of Plant Diseases by Leaf Image Classification," *Comput. Intell. Neurosci.*, vol. 2016, 2016, doi: 10.1155/2016/3289801.

[14] C. Rother, V. Kolmogorov, and A. Blake, "'GrabCut,'," *ACM Trans. Graph.*, vol. 23, no. 3, pp. 309–314, 2004, doi: 10.1145/1015706.1015720.

[15] Y. Li, J. Zhang, P. Gao, L. Jiang, and M. Chen, "Grab Cut Image Segmentation Based on Image Region," *2018 3rd IEEE Int. Conf. Image, Vis. Comput. ICIVC 2018,*. pp. 311–315, 2018, doi: 10.1109/ICIVC.2018.8492818.

[16] G. Saravanan, G. Yamuna, and S. Nandhini, and M. Jagersand, "Real time implementation of RGB to HSV/HSI/HSL and its reverse color space models," *Int. Conf. Commun. Signal Process. ICCSP 2016*, pp. 462–466, 2016, doi: 10.1109/ICCSP.2016.7754179.

[17] L. Feng, H. Li, Y. Gao, and Y. Zhang, "A Color Image Segmentation Method Based on Region Salient Color and Fuzzy C-Means Algorithm," *Circuits, Syst. Signal Process.*, vol. 39, no. 2, pp. 586–610, 2020, doi: 10.1007/s00034-019-01126-w.

[18] K. Szyc, "An Impact of Different Images Color Spaces on the Efficiency of Convolutional Neural Networks," in *Engineering in Dependability of Computer Systems and Networks*, 2020, pp. 506–514.

[19] N. John, A. Viswanath, V. Sowmya, and K. P. Soman, "Analysis of Various Color Space Models on Effective Single Image Super Resolution," in *Intelligent Systems Technologies and Applications*, 2016, pp. 529–540.

[20] J. Shijie, W. Ping, J. Peiyi dan H. Siping, "Research on Data Augmentation for Image Classification Based on Convolution Neural Networks," *Proceedings - 2017 Chinese Automation Congress, CAC 2017*, vol. 2017-January, no. 201602118, pp. 4165–4170, 2017, doi: 10.1109/CAC.2017.8243510.

[21] T. Guo, J. Dong, and Gao, "Simple Convolutional Neural Network on Image Classification," *IEEE 2nd Int. Conf. Big Data Anal.*, pp. 721–724, 2017.

[22] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, vol. 1 2016-December, pp. 770–778, 2016, doi: 10.1109/CVPR.2016.90.

[23] P. Kamsing, P. Torteeka, and S. Yooyen, "Deep Convolutional Neural Networks for plane identification on Satellite imagery by exploiting transfer learning with a different optimizer," *Int. Geosci. Remote Sens. Symp.*, pp. 9788–9791, 2019, doi: 10.1109/IGARSS.2019.8899206.

[24] M. N. Halgamuge, E. Daminda, and A. Nirmalathas, "Best optimizer selection for predicting bushfire occurrences using deep learning," *Nat. Hazards*, vol. 103, no. 1, pp. 845–860, 2020, doi: 10.1007/s11069-020-04015-7.