

DAFTAR PUSTAKA

- [1] M. A. Hannan, M. M. Hoque, A. Hussain, Y. Yusof and P. J. Ker, "State-of-the-Art and Energy Management System of Lithium-Ion Batteries in Electric Vehicle Applications: Issues and Recommendations," in *IEEE Access*, vol. 6, pp. 19362-19378, 2018, doi: 10.1109/ACCESS.2018.2817655.
- [2] R. Xiong, Y. Zhang, J. Wang, H. He, S. Peng and M. Pecht, "Lithium-Ion Battery Health Prognosis Based on a Real Battery Management System Used in Electric Vehicles," in *IEEE Transactions on Vehicular Technology*, vol. 68, no. 5, pp. 4110-4121, May 2019, doi: 10.1109/TVT.2018.2864688.
- [3] G. Fathoni, S. A. Widayat, P. A. Topan, A. Jalil, A. I. Cahyadi and O. Wahyunggoro, "Comparison of State-of-Charge (SOC) estimation performance based on three popular methods: Coulomb counting, open circuit voltage, and Kalman filter," *2017 2nd International Conference on Automation, Cognitive Science, Optics, Micro Electro-Mechanical System, and Information Technology (ICACOMIT)*, Jakarta, 2017, pp. 70-74, doi: 10.1109/ICACOMIT.2017.8253389.
- [4] C. Wu, J. Sun, C. Zhu, Y. Ge and Y. Zhao, "Research on Overcharge and Overdischarge Effect on Lithium-Ion Batteries," *2015 IEEE Vehicle Power and Propulsion Conference (VPPC)*, Montreal, QC, 2015, pp. 1-6, doi: 10.1109/VPPC.2015.7353006.
- [5] Govaers, Felix, ed. *Introduction and Implementations of the Kalman Filter*. BoD–Books on Demand, 2019, doi: 10.5772/intechopen.75731
- [6] McRoberts, Michael. *Beginning Arduino*. Apress, 2013, doi : 10.1007/978-1-4302-5017-3.
- [7] ACS712, Datasheet. "Fully Integrated, Hall Effect-Based Linear Current Sensor IC with 2.1 kVRMS Isolation and a Low-Resistance Current Conductor." (2006).
- [8] Slomovitz, D., et al. "Resistor dividers for power quality meters." *2016 Conference on Precision Electromagnetic Measurements (CPEM 2016)*. IEEE, 2016.
- [9] Datasheet, DS18B20. "Maxim Integrated Products." *Inc*, <http://www.maxim-ic.com> (2004)
- [10] Xiamen Amotec Display CO, "Specifications of LCD Module.", 2008

- [11] Ting, T. O., et al. "State-of-Charge for Battery Management System via Kalman Filter." *Engineering Letters* 22.2 (2014).
- [12] Guo, Dong, and Liangzong He. "A Novel Algorithm for SOC using Simple Iteration and Coulomb Counting Method." *2018 IEEE Student Conference on Electric Machines and Systems*. IEEE, 2018.
- [13] A. C. Hua and B. Z. Syue, "Charge and discharge characteristics of lead-acid battery and LiFePO₄ battery," *The 2010 International Power Electronics Conference - ECCE ASIA -*, Sapporo, 2010, pp. 1478-1483, doi: 10.1109/IPEC.2010.5544506.
- [14] Chai, Tianfeng, and Roland R. Draxler. "Root mean square error (RMSE) or mean absolute error (MAE)?—Arguments against avoiding RMSE in the literature." *Geoscientific model development* 7.3 (2014): 1247-1250.
- [15] Loukil, Jihen, Ferdaous Masmoudi, and Nabil Derbel. "State of charge estimation of lead acid battery using a Kalman filter." *2017 14th International Multi-Conference on Systems, Signals & Devices (SSD)*. IEEE, 2017.