

DAFTAR PUSTAKA

- [1] I. N. Haq *et al.*, “Development of battery management system for cell monitoring and protection,” *Proc. 2014 Int. Conf. Electr. Eng. Comput. Sci. ICEECS 2014*, no. November, pp. 203–208, 2014, doi: 10.1109/ICEECS.2014.7045246.
- [2] K. W. E. Cheng, B. P. Divakar, H. Wu, K. Ding, and H. F. Ho, “Battery-management system (BMS) and SOC development for electrical vehicles,” *IEEE Trans. Veh. Technol.*, vol. 60, no. 1, pp. 76–88, 2011, doi: 10.1109/TVT.2010.2089647.
- [3] H. Kato, Y. Yamamoto, M. Nagamine, and Y. Nishi, “Lithium ion rechargeable batteries,” *Proc. WESCON 1993 Conf. Rec.*, pp. 210–214, 1993, doi: 10.1109/WESCON.1993.488436.
- [4] S. W. Moore and P. J. Schneider, “SAE TECHNICAL A Review of Cell Equalization Methods for Lithium Ion and Lithium Polymer Battery Systems,” *sae Tech. Pap. Ser.*, no. 724, p. 1607, 2018.
- [5] J. Chatzakis, K. Kalaitzakis, N. C. Voulgaris, and S. N. Manias, “Designing a new generalized battery management system,” *IEEE Trans. Ind. Electron.*, vol. 50, no. 10, pp. 990–999, 2003, doi: 10.1109/TIE.2003.817706.
- [6] “Индукция Интерферонов 1-, 2- И 3-Го Типов Солями Акридонуксусной Кислоты,” *Sist. KONTROL Charg. DAN DISCHARGING SERTA Monit. Kesehat. BATERAI*, vol. 59, no. 9–10, 2020.
- [7] L. Buccolini, A. Ricci, C. Scavongelli, G. Demaso-Gentile, S. Orcioni, and M. Conti, “Battery Management System (BMS) simulation environment for electric vehicles,” *EEEIC 2016 - Int. Conf. Environ. Electr. Eng.*, pp. 2–7, 2016, doi: 10.1109/EEEIC.2016.7555475.
- [8] Z. B. Omariba, L. Zhang, and D. Sun, “Review of Battery Cell Balancing Methodologies for Optimizing Battery Pack Performance in Electric Vehicles,” *IEEE Access*, vol. 20, pp. 129335–129352, 2017, doi: 10.1109/ACCESS.2019.2940090.
- [9] X. Hu, H. Yuan, C. Zou, Z. Li, and L. Zhang, “Co-Estimation of State of Charge

- and State of Health for Lithium-Ion Batteries Based on Fractional-Order Calculus,” *IEEE Trans. Veh. Technol.*, vol. 67, no. 11, pp. 10319–10329, 2018, doi: 10.1109/TVT.2018.2865664.
- [10] W.-Y. Chang, “The State of Charge Estimating Methods for Battery: A Review,” *ISRN Appl. Math.*, vol. 2013, no. 1, pp. 1–7, 2013, doi: 10.1155/2013/953792.
- [11] K. S. Ng, C. S. Moo, Y. P. Chen, and Y. C. Hsieh, “Enhanced coulomb counting method for estimating state-of-charge and state-of-health of lithium-ion batteries,” *Appl. Energy*, vol. 86, no. 9, pp. 1506–1511, 2009, doi: 10.1016/j.apenergy.2008.11.021.
- [12] W. Suryono, A. Setiyo Prabowo, Suhanto, and A. Mu’Ti Sazali, “Monitoring and controlling electricity consumption using Wemos D1 Mini and smartphone,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 909, no. 1, 2020, doi: 10.1088/1757-899X/909/1/012014.
- [13] H. T. Monda, F. Feriyonika, and P. S. Rudati, “Sistem Pengukuran Daya pada Sensor Node Wireless Sensor Network,” *Pros. Ind. Res. Work. Natl. Semin.*, vol. 9, pp. 28–31, 2018.
- [14] A. Setiawan and O. C. Pritiwi, “Sprayer Hand Sanitizer Nirsentuh Menggunakan Infra Red (IR) Obstacle Avoidance Sensor Berbasis Arduino Uno,” *Pros. Semin. Nas. Fis. 6.0*, vol. 0, pp. 222–226, 2020.
- [15] W. D. Fang, W. He, W. Chen, L. H. Shan, and F. Y. Ma, “Research on the application-driven architecture in internet of things,” *Front. Artif. Intell. Appl.*, vol. 293, pp. 458–465, 2016, doi: 10.3233/978-1-61499-722-1-458.
- [16] B. Bohara, S. Maharjan, and B. R. Shrestha, “IoT Based Smart Home using Blynk Framework,” vol. 1, no. 1, pp. 26–30, 2020, [Online]. Available: <http://arxiv.org/abs/2007.13714>.
- [17] N. A. Z. M. Noar and M. M. Kamal, “The development of smart flood monitoring system using ultrasonic sensor with blynk applications,” *2017 IEEE Int. Conf. Smart Instrumentation, Meas. Appl. ICSIMA 2017*, vol. 2017-Novem, no. November, pp. 1–6, 2018, doi: 10.1109/ICSIMA.2017.8312009.