

BIBLIOGRAPHY

- [1] K. A. Aldhlan, A. M. Zeki, A. M. Zeki, and H. A. Alreshidi, “Novel mechanism to improve hadith classifier performance,” in *Proceedings - 2012 International Conference on Advanced Computer Science Applications and Technologies, ACSAT 2012*, 2013, pp. 512–517, doi: 10.1109/ACSAT.2012.93.
- [2] M. N. Al-Kabi, K. Ghassan, R. Al-Shalabi, S. I. Al-Sinjalawi, and R. S. Al-Mustafa, “Al-Hadith Text Classifier,” *Journal of Applied Sciences*, vol. 5, no. 3, pp. 584–587, 2005, doi: 10.3923/jas.2005.584.587.
- [3] F. Harrag and E. El-Qawasmah, “Neural network for Arabic text classification,” *2nd International Conference on the Applications of Digital Information and Web Technologies, ICADIWT 2009*, pp. 778–783, 2009, doi: 10.1109/ICADIWT.2009.5273841.
- [4] H. Fauzan, A. Adiwijaya, and S. Al-Faraby, “Pengklasifikasian Topik Hadits Terjemahan Bahasa Indonesia Menggunakan Latent Semantic Indexing dan Support Vector Machine,” *Jurnal Media Informatika Budidarma*, vol. 2, no. 4, p. 131, 2018, doi: 10.30865/mib.v2i4.948.
- [5] D. C. Hidayati, S. Al Faraby, and A. Adiwijaya, “Klasifikasi Topik Multi Label pada Hadis Shahih Bukhari Menggunakan K-Nearest Neighbor dan Latent Semantic Analysis,” *JURIKOM (Jurnal Riset Komputer)*, vol. 7, no. 1, p. 140, 2020, doi: 10.30865/jurikom.v7i1.2013.
- [6] M. Y. Abu Bakar, Adiwijaya, and S. Al Faraby, “Multi-Label Topic Classification of Hadith of Bukhari (Indonesian Language Translation)Using Information Gain and Backpropagation Neural Network,” *Proceedings of the 2018 International Conference on Asian Language Processing,IALP 2018*, pp. 344–350, 2019, doi: 10.1109/IALP.2018.8629263.
- [7] S. Al Faraby, E. R. R. Jasin, A. Kusumaningrum, and Adiwijaya, “Classification of hadith into positive suggestion, negative suggestion, and information,” *Journal of Physics: Conference Series*, vol. 971, no. 1, 2018, doi: 10.1088/1742-6596/971/1/012046.
- [8] F. S. Al-Anzi and D. AbuZeina, “Toward an enhanced Arabic text classification using cosine similarity and Latent Semantic Indexing,” *Journal of King Saud University - Computer and Information Sciences*, vol. 29, no. 2, pp. 189–195, 2017, doi: 10.1016/j.jksuci.2016.04.001.
- [9] G. Mediamer, adiwijaya@telkomuniversity.ac.id Adiwijaya, and S. Al Faraby,

- “Development of rule-based feature extraction in multi-label text classification,” *International Journal on Advanced Science, Engineering and Information Technology*, vol. 9, no. 4, pp. 1460–1465, 2019, doi: 10.18517/ijaseit.9.4.8894.
- [10] M. D. Purbolaksono, F. D. Reskyadita, Adiwijaya, A. A. Suryani, and A. F. Huda, “Indonesian text classification using back propagation and sastrawi stemming analysis with information gain for selection feature,” *International Journal on Advanced Science, Engineering and Information Technology*, vol. 10, no. 1, pp. 234–238, 2020, doi: 10.18517/ijaseit.10.1.8858.
- [11] R. Li, W. Liu, Y. Lin, H. Zhao, and C. Zhang, “An Ensemble Multilabel Classification for Disease Risk Prediction,” *Journal of Healthcare Engineering*, vol. 2017, 2017, doi: 10.1155/2017/8051673.
- [12] G. Chen, D. Ye, Z. Xing, J. Chen, and E. Cambria, “Ensemble application of convolutional and recurrent neural networks for multi-label text categorization,” *Proceedings of the International Joint Conference on Neural Networks*, vol. 2017-May, pp. 2377–2383, 2017, doi: 10.1109/IJCNN.2017.7966144.
- [13] I. Hmeidi, M. Al-Ayyoub, N. A. Abdulla, A. A. Almodawar, R. Abooraig, and N. A. Mahyoub, “Automatic Arabic text categorization: A comprehensive comparative study,” *Journal of Information Science*, vol. 41, no. 1, pp. 114–124, Feb. 2015, doi: 10.1177/0165551514558172.
- [14] R. H. W. Pinheiro, G. D. C. Cavalcanti, and T. I. Ren, “Data-driven global-ranking local feature selection methods for text categorization,” *Expert Systems with Applications*, vol. 42, no. 4, pp. 1941–1949, 2015, doi: 10.1016/j.eswa.2014.10.011.
- [15] S. Shimpikar and S. Govilkar, “A Survey of Text Summarization Techniques for Indian Regional Languages,” *International Journal of Computer Applications*, vol. 165, no. 11, pp. 29–33, 2017, doi: 10.5120/ijca2017914083.
- [16] R. Johnson and T. Zhang, “Semi-supervised convolutional neural networks for text categorization via region embedding,” *Advances in Neural Information Processing Systems*, vol. 2015-Janua, pp. 919–927, 2015.
- [17] X. Zhang, J. Zhao, and Y. LeCun, “Character-level Convolutional Networks for Text Classification,” *Advances in Neural Information Processing Systems*, pp. 649–657, 2015.
- [18] H. Liang, X. Sun, Y. Sun, and Y. Gao, “Text feature extraction based on deep learning: a review,” *Eurasip Journal on Wireless Communications and Networking*, vol. 2017, no. 1, pp. 1–12, 2017, doi: 10.1186/s13638-017-0993-1.
- [19] W. Hu, Y. Huang, L. Wei, F. Zhang, and H. Li, “Deep Convolutional Neural Networks for Hyperspectral Image Classification,” *Journal of Sensors*, vol. 2015, pp.

- 1–12, 2015, doi: 10.1155/2015/258619.
- [20] J. D. Prusa and T. M. Khoshgoftaar, “Improving deep neural network design with new text data representations,” *Journal of Big Data*, vol. 4, no. 1, 2017, doi: 10.1186/s40537-017-0065-8.
- [21] B. Wang, “Disconnected recurrent neural networks for text categorization,” *ACL 2018 - 56th Annual Meeting of the Association for Computational Linguistics, Proceedings of the Conference (Long Papers)*, vol. 1, pp. 2311–2320, 2018, doi: 10.18653/v1/p18-1215.
- [22] S. S. Talathi and A. Vartak, “Improving performance of recurrent neural network with relu nonlinearity,” 2015.
- [23] A. Abdi, S. M. Shamsuddin, S. Hasan, and J. Piran, “Deep learning-based sentiment classification of evaluative text based on Multi-feature fusion,” *Information Processing and Management*, vol. 56, no. 4, pp. 1245–1259, 2019, doi: 10.1016/j.ipm.2019.02.018.
- [24] B. Chen, Q. Huang, Y. Chen, L. Cheng, and R. Chen, “Deep Neural Networks for Multi-class Sentiment Classification,” *Proceedings - 20th International Conference on High Performance Computing and Communications, 16th International Conference on Smart City and 4th International Conference on Data Science and Systems, HPCC/SmartCity/DSS 2018*, pp. 854–859, 2019, doi: 10.1109/HPCC/SmartCity/DSS.2018.00142.
- [25] Y. Luo, “Recurrent neural networks for classifying relations in clinical notes,” *Journal of Biomedical Informatics*, vol. 72, pp. 85–95, 2017, doi: 10.1016/j.jbi.2017.07.006.
- [26] S. Li, W. Li, C. Cook, C. Zhu, and Y. Gao, “A fully trainable network with RNN-based pooling,” *Neurocomputing*, vol. 338, no. Shuai Li, pp. 72–82, 2019, doi: 10.1016/j.neucom.2019.02.004.
- [27] S. Lai, L. Xu, K. Liu, and J. Zhao, “Recurrent convolutional neural networks for text classification,” *Proceedings of the National Conference on Artificial Intelligence*, vol. 3, pp. 2267–2273, 2015.
- [28] M. Sivaram, V. Porkodi, A. S. Mohammed, and V. Manikandan, “Detection of accurate facial detection using hybrid deep convolutional recurrent neural network,” pp. 1844–1850, 2019, doi: 10.21917/ijsc.2019.0256.
- [29] K. Choi, G. Fazekas, M. Sandler, and K. Cho, “Convolutional recurrent neural networks for music classification,” in *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2017, pp. 2392–2396, doi: 10.1109/ICASSP.2017.7952585.

- [30] R. Wang, Z. Li, J. Cao, T. Chen, and L. Wang, “Convolutional Recurrent Neural Networks for Text Classification,” *Proceedings of the International Joint Conference on Neural Networks*, vol. 2019-July, no. 2018, pp. 1–6, 2019, doi: 10.1109/IJCNN.2019.8852406.
- [31] J. Zhang, S. Shan, M. Kan, and X. Chen, “Coarse-to-Fine Auto-Encoder Networks (CFAN) for Real-Time Face Alignment,” 2014, pp. 1–16.
- [32] J. deng, Y. Sun, Q. Liu, and H. Lu, “Low rank driven robust facial landmark regression,” *Neurocomputing*, vol. 151, no. P1, pp. 196–206, Mar. 2015, doi: 10.1016/j.neucom.2014.09.052.
- [33] Z. Zhang, P. Luo, C. C. Loy, and X. Tang, “Facial Landmark Detection by Deep Multi-task Learning,” in *Proceedings of International Conference on European Conference on Computer Vision*, 2014, pp. 94–108, doi: 10.1007/978-3-319-10599-4_7.
- [34] X. P. Burgos-Artizzu, P. Perona, and P. Dollar, “Robust Face Landmark Estimation under Occlusion,” in *2013 IEEE International Conference on Computer Vision*, 2013, pp. 1513–1520, doi: 10.1109/ICCV.2013.191.
- [35] R. Yamashita, M. Nishio, R. K. G. Do, and K. Togashi, “Convolutional neural networks: an overview and application in radiology,” *Insights into Imaging*, vol. 9, no. 4, pp. 611–629, 2018, doi: 10.1007/s13244-018-0639-9.
- [36] A. Krizhevsky, I. Sutskever, and G. E. Hinton, “ImageNet classification with deep convolutional neural networks,” *Communications of the ACM*, vol. 60, no. 6, pp. 84–90, May 2017, doi: 10.1145/3065386.
- [37] Y. LeCun, Y. Bengio, and G. Hinton, “Deep learning,” *Nature*, vol. 521, no. 7553, pp. 436–444, May 2015, doi: 10.1038/nature14539.
- [38] H. Ide and T. Kurita, “Improvement of learning for CNN with ReLU activation by sparse regularization,” *Proceedings of the International Joint Conference on Neural Networks*, vol. 2017-May, pp. 2684–2691, 2017, doi: 10.1109/IJCNN.2017.7966185.
- [39] B. Karlik and V. A. Olgac, “Performance Analysis of Various Activation Functions in Artificial Neural Networks,” *International Journal of Artificial Intelligence And Expert Systems (IJAE)*, vol. 1, no. 4, pp. 111–122, Jun. 2011, doi: 10.1088/1742-6596/1237/2/022030.
- [40] A. F. Agarap, “Deep Learning using Rectified Linear Units (ReLU),” no. 1, pp. 2–8, 2018.
- [41] C. Nwankpa, W. Ijomah, A. Gachagan, and S. Marshall, “Activation Functions: Comparison of trends in Practice and Research for Deep Learning,” pp. 1–20, 2018.
- [42] Z. Zuo *et al.*, “Convolutional recurrent neural networks: Learning spatial

- dependencies for image representation,” *IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, vol. 2015-Octob, pp. 18–26, 2015, doi: 10.1109/CVPRW.2015.7301268.
- [43] S. Sigtia, E. Benetos, and S. DIxon, “An end-to-end neural network for polyphonic piano music transcription,” *IEEE/ACM Transactions on Audio Speech and Language Processing*, vol. 24, no. 5, pp. 927–939, 2016, doi: 10.1109/TASLP.2016.2533858.
- [44] T. Mikolov, K. Chen, G. Corrado, and J. Dean, “Efficient estimation of word representations in vector space,” *1st International Conference on Learning Representations, ICLR 2013 - Workshop Track Proceedings*, pp. 1–12, 2013.
- [45] J. Pennington, R. Socher, and C. Manning, “Glove: Global Vectors for Word Representation,” in *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2014, vol. 19, no. 5, pp. 1532–1543, doi: 10.3115/v1/D14-1162.
- [46] P. Bojanowski, E. Grave, A. Joulin, and T. Mikolov, “Enriching Word Vectors with Subword Information,” *Transactions of the Association for Computational Linguistics*, vol. 5, pp. 135–146, 2017, doi: 10.1162/tacl_a_00051.
- [47] N. Ketkar, *Deep Learning with Python*. Berkeley, CA: Apress, 2017.
- [48] K. Yang, H. Wang, G. Dai, S. Hu, Y. Zhang, and J. Xu, “Determining the repeat number of cross-validation,” *Proceedings - 2011 4th International Conference on Biomedical Engineering and Informatics, BMEI 2011*, vol. 3, pp. 1706–1710, 2011, doi: 10.1109/BMEI.2011.6098566.