

## LIST OF FIGURES

2.1	Node sensor scattered in sensor field . . . . .	5
2.2	Passive attack (traffic analysis) . . . . .	8
2.3	Active Attacks (Modifications of messages) . . . . .	9
2.4	Specifications of the J-PAKE protocol . . . . .	13
3.1	The Communication on WSN . . . . .	15
3.2	Flowchart System Model . . . . .	16
3.3	Flowchart Authentication of New Node . . . . .	18
3.4	Process of obtaining session key . . . . .	19
3.5	Process of authentication process on ECDH . . . . .	19
4.1	Changes in the number of nodes 25, 50, 100, 200, 400 with gm number 4 . . . . .	22
4.2	Everage energy against node changes . . . . .	22
4.3	Change in gm number 2, 4, 6, 8, 10 with 100 nodes . . . . .	23
4.4	Everage energy against GM changes . . . . .	24
4.5	Computation time . . . . .	26
1.1	Nodes scattered in the map . . . . .	1
1.2	Used Scenario . . . . .	1
1.3	Used Scenario . . . . .	2
1.4	Used Scenario . . . . .	3
1.5	Used Scenario . . . . .	3
1.6	Simulation Result 5 group, 20 node, time 10000 seconds . . . . .	4
1.7	Simulation Result 5 group, 20 node, time 20000 seconds . . . . .	4
1.8	Simulation Result 5 group, 20 node, time 43200 seconds . . . . .	5
1.9	Simulation Result 5 group, 20 node, time 86400 seconds . . . . .	5