

# DAFTAR ISI

**LEMBAR PENGESAHAN**

**LEMBAR PERNYATAAN ORISINALITAS**

**ABSTRAK** **iv**

**KATA PENGANTAR** **vi**

**DAFTAR ISI** **ix**

**DAFTAR GAMBAR** **xii**

**DAFTAR TABEL** **xiv**

**DAFTAR SINGKATAN** **xv**

**I PENDAHULUAN** **1**

1.1 Latar Belakang Masalah . . . . . 1

1.2 Rumusan Masalah . . . . . 2

1.3 Tujuan dan Manfaat . . . . . 2

1.4 Batasan Masalah . . . . . 3

1.5 Metode Penelitian . . . . . 3

1.6 Sistematika Penulisan . . . . . 4

**DAFTAR LAMPIRAN** **1**

**II DASAR TEORI** **6**

2.1 *Long Term Evolution* (LTE) . . . . . 6

2.1.1 Arsitektur LTE . . . . . 6

	x
2.2 <i>Radio Access Network (RAN)</i> . . . . .	8
2.2.1 <i>Arsitektur RAN</i> . . . . .	8
2.3 <i>Functional Split RAN</i> . . . . .	11
2.4 <i>Open RAN</i> . . . . .	12
2.4.1 <i>Arsitektur Open RAN</i> . . . . .	13
2.4.2 <i>Unit dan Node Fungsional Open RAN</i> . . . . .	14
2.5 <i>Orthogonal Frequency Division Multiple Access (OFDMA)</i> . . . . .	15
2.6 <i>The Third Generation Partnership Project (3GPP)</i> . . . . .	16
2.7 <i>Parameter Kualitas Jaringan</i> . . . . .	16
2.7.1 <i>Reference Signal Received Power (RSRP)</i> . . . . .	16
2.7.2 <i>Signal to Interference plus Noise Ratio (SINR)</i> . . . . .	17
2.8 <i>Resource Block (RB)</i> . . . . .	17
2.9 <i>Throughput</i> . . . . .	18
2.9.1 <i>Throughput pada Penelitian</i> . . . . .	18
2.10 <i>Channel Quality Indicator (CQI)</i> . . . . .	19
2.11 <i>Modulation and Coding Scheme (MCS)</i> . . . . .	20
<b>III PERANCANGAN SISTEM</b>	<b>24</b>
3.1 <i>Diagram Alir Penelitian</i> . . . . .	24
3.2 <i>Lokasi Drive Test</i> . . . . .	25
3.3 <i>Parameter Input</i> . . . . .	26
3.4 <i>Perhitungan Throughput 3GPP</i> . . . . .	26
3.4.1 <i>Logfile Simulasi</i> . . . . .	26
3.4.2 <i>Hasil Plotting Simulasi Throughput</i> . . . . .	27
3.4.3 <i>Proses Perhitungan Throughput 3GPP</i> . . . . .	28
<b>IV HASIL SIMULASI DAN ANALISIS</b>	<b>30</b>
4.1 <i>Tinjauan Umum</i> . . . . .	30
4.2 <i>Hasil Pengukuran Skenario 1</i> . . . . .	30

4.2.1	<i>Reference Signal Received Power (RSRP)</i> . . . . .	30
4.2.2	<i>Signal to Interference plus Noise Ratio (SINR)</i> . . . . .	31
4.2.3	<i>Channel Quality Indicator (CQI)</i> . . . . .	32
4.2.4	<i>Modulation and Coding Scheme (MCS)</i> . . . . .	32
4.2.5	<i>Throughput</i> . . . . .	33
4.3	Hasil Simulasi Skenario 2 . . . . .	34
4.3.1	<i>Reference Signal Received Power (RSRP)</i> . . . . .	35
4.3.2	<i>Signal to Interference plus Noise Ratio (SINR)</i> . . . . .	35
4.3.3	<i>Channel Quality Indicator (CQI)</i> . . . . .	36
4.3.4	<i>Modulation and Coding Scheme (MCS)</i> . . . . .	37
4.3.5	<i>Throughput</i> . . . . .	37
4.4	Rekapitulasi Hasil Simulasi . . . . .	39
4.5	Analisis Perbandingan <i>Throughput Real</i> dan 3GPP . . . . .	39
4.5.1	Perbandingan dengan Skenario 1 . . . . .	39
4.5.2	Perbandingan dengan Skenario 2 . . . . .	40
4.6	Rekapitulasi Hasil Perbandingan <i>Throughput</i> . . . . .	41
4.6.1	Rekapitulasi Terhadap Skenario 1 . . . . .	41
4.6.2	Rekapitulasi Terhadap Skenario 2 . . . . .	42
<b>V</b>	<b>KESIMPULAN DAN SARAN</b>	<b>44</b>
5.1	Kesimpulan . . . . .	44
5.2	Saran . . . . .	45
	<b>DAFTAR PUSTAKA</b>	<b>46</b>
	<b>LAMPIRAN</b>	
<b>A</b>	<b>Perangkat Open RAN</b>	