

DAFTAR SINGKATAN

μs	: <i>Microseconds</i>
ADC	: <i>Analog to Digital Converter</i>
CLK	: <i>Clock (pulse)</i>
cm/s	: <i>Centimeter/seconds</i>
CMD	: <i>Command</i>
CMOS	: <i>Complementary Metal-Oxide Semiconductor</i>
DC	: <i>Direct Current</i>
EN	: <i>Equivalent Node</i>
GND	: <i>Ground</i>
GPIO	: <i>General-Purpose Input/Output</i>
I ² C / IIC	: <i>Inter-Integrated Circuit bus</i>
IoT	: <i>Internet of Things</i>
kg/cm	: <i>Kilogram/centimeter</i>
kHz	: <i>kilohertz</i>
LCD	: <i>Liquid Cristal Display</i>
m/s	: <i>Meter/seconds</i>
MANET	: <i>Mobile Ad-Hoc Network</i>
MEMS	: <i>Microelectromechanical</i>
mm	: <i>milimeter</i>
PWM	: <i>Pulse Width Modulation</i>
QR Code	: <i>Quick Response Code</i>
RFID	: <i>Radio Frequency Identification</i>
RST	: <i>Readability Signal Strength-Tone</i>

RX	: <i>Reciever</i>
SCL	: <i>Serial Clock</i>
SDA	: <i>Serial Data</i>
SPI	: <i>Serial Peripheral Interface</i>
TX	: <i>Transmitter</i>
UART	: <i>Universal Asynchronous Reciever-Transmitter</i>
USB	: <i>Universal Serial Bus</i>
Vin	: <i>Vehicle Identification Number</i>
VR	: <i>Variabel Resistor</i>