

DAFTAR SINGKATAN

A	: <i>Ampere</i>
AC	: <i>Air Conditioner</i>
ac	: <i>Alternating current</i>
ACB	: <i>Air circuit breaker</i>
AH	: <i>Ampere Hour</i>
AMP	: <i>Ampere</i>
BHSA	: <i>Busy Hour Service AttemPA</i>
BLER	: <i>Block Error Rate</i>
BS	: <i>Base Station</i>
C	: <i>Coloumb</i>
C	: <i>Celcius</i>
dB	: <i>Decibel</i>
dBm	: <i>Decibel Milliwatt</i>
dc	: <i>direct current</i>
dc PDB	: <i>Direct Current Panel Distribution Board</i>
DEG	: <i>Diesel Engine Generator</i>
EIRP	: <i>Effective Isotropic Radiated Power</i>
EPC	: <i>Evolved Packet Core</i>
E-UTRAN	: <i>Evolved UMTS Terrestrial Radio Access Network</i>
FDD	: <i>Frequency Division Duplex</i>
HSS	: <i>Home Subscriber Server</i>
IMB	: <i>Izin Mendirikan Bangunan</i>
KPI	: <i>Key Performance Indicator</i>
LTE	: <i>Long Term Evolution</i>
MA	: <i>Milli Ampere</i>
MAPL	: <i>Maximum Allowable Path Loss</i>
Mbps	: <i>Megabit per second</i>
MHz	: <i>Megahertz</i>
MIMO	: <i>Multiple Input and Multiple Output</i>
MME	: <i>Mobile Management Entity</i>
MS	: <i>Mobile Station</i>

MV	: Millivolt
OFDMA	: Orthogonal Frequency Division Multiple Access
OSS	: Operating Support System
PAR	: Peak to Average Ratio
PCI	: Physical Cell Identity
PCRF	: Policy Control and Rules Function
P-GW	: Packet Data Network Gateway
QAM	: Quadrature Amplitude Modulation
QPSK	: Quadrature Phase Shift Keying
RF	: Radio Frequency
RSRP	: Reference Signal Received Power
SC-FDMA	: Single Carrier Frequency Division Multiple Access
S-GW	: Serving Gateway
SINR	: Signal to Interference Noise Ratio
Temp	: Temperature
UE	: User Equipment
UPS	: Uninterruptable Power Supply
V	: Voltage
VA	: Volt Ampere
Vac	: Voltage Alternating Current
V/C	: Volt/Cell
Vdc	: Voltage direct current
W	: Watt
WH	: Watt hour