



## REFERENCES

- [1] S. H. Nasr, C. K. Dagli, M. M. Dakake, J. E. B. Lombard, and M. Rustom, “The Study Quran,” *A new Transl. Comment.*, vol. 19, 2015.
- [2] R. Grishman and B. M. Sundheim, “Message understanding conference-6: A brief history,” 1996.
- [3] D. Nadeau and S. Sekine, “A survey of named entity recognition and classification,” *Linguisticae Investig.*, vol. 30, no. 1, pp. 3–26, 2007.
- [4] V. Yadav and S. Bethard, “A survey on recent advances in named entity recognition from deep learning models,” *arXiv Prepr. arXiv1910.11470*, 2019.
- [5] J. Lafferty, A. McCallum, and F. C. N. Pereira, “Conditional random fields: Probabilistic models for segmenting and labeling sequence data,” 2001.
- [6] Z. Huang, W. Xu, and K. Yu, “Bidirectional LSTM-CRF models for sequence tagging,” *arXiv Prepr. arXiv1508.01991*, 2015.
- [7] B. Wilie *et al.*, “IndoNLU: Benchmark and resources for evaluating Indonesian natural language understanding,” *arXiv Prepr. arXiv2009.05387*, 2020.
- [8] A. Vaswani *et al.*, “Attention is all you need,” in *Advances in neural information processing systems*, 2017, pp. 5998–6008.
- [9] L. A. Ramshaw and M. P. Marcus, “Text chunking using transformation-based learning,” in *Natural language processing using very large corpora*, Springer, 1999, pp. 157–176.
- [10] E. F. Sang and F. De Meulder, “Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition,” *arXiv Prepr. cs/0306050*, 2003.
- [11] P. Q. N. Minh, “A feature-based model for nested named-entity recognition at VLSP-2018 ner evaluation campaign,” *arXiv Prepr. arXiv1803.08463*, 2018.
- [12] A. Akbik, T. Bergmann, D. Blythe, K. Rasul, S. Schweter, and R. Vollgraf, “FLAIR: An easy-to-use framework for state-of-the-art NLP,” in *{NAACL} 2019, 2019 Annual Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, 2019, pp. 54–59.
- [13] T. Mikolov, I. Sutskever, K. Chen, G. S. Corrado, and J. Dean, “Distributed representations of words and phrases and their compositionality,” *Adv. Neural Inf. Process. Syst.*, vol. 26, 2013.
- [14] P. Bojanowski, E. Grave, A. Joulin, and T. Mikolov, “Enriching Word Vectors with Subword Information,” *Trans. Assoc. Comput. Linguist.*, vol. 5, pp. 135–146, 2017.
- [15] E. Grave, P. Bojanowski, P. Gupta, A. Joulin, and T. Mikolov, “Learning Word Vectors for 157 Languages,” 2018.
- [16] J. Pennington, R. Socher, and C. D. Manning, “GloVe: Global Vectors for Word Representation,” in *Empirical Methods in Natural Language Processing (EMNLP)*, 2014, pp. 1532–1543. [Online]. Available: <http://www.aclweb.org/anthology/D14-1162>
- [17] H. Nakayama, “{seqeval}: A Python framework for sequence labeling evaluation.” 2018. [Online]. Available: <https://github.com/chakki-works/seqeval>