

## DAFTAR PUSTAKA

- Airao, J., Khanna, N., Roy, A., & Hegab, H. (2020). Comprehensive experimental analysis and sustainability assessment of machining Nimonic 90 using ultrasonic-assisted turning facility. *The International Journal of Advanced Manufacturing Technology*, 1447–1462. <https://doi.org/10.1007/s00170-020-05686-z>/Published
- Asha, P. B., Rao, P., & Kumar, R. (2018). Effect Of Machining Parameters On Cutting Tool Temperature And Tool Life While Turning EN24 And Hchr Grade Alloy Steel. In *Materials Today: Proceedings* (Vol. 5). [www.sciencedirect.com](http://www.sciencedirect.com)[www.materialstoday.com/proceedings](http://www.materialstoday.com/proceedings)
- Balaji, S., Selvakumar, C., Sukanya, G., Muruganandham, V. R., & Devan, P. D. (2022). Investigation and optimization of turning process parameters in super duplex stainless steel. *Materials Today: Proceedings*, 62, 1925–1928. <https://doi.org/10.1016/J.MATPR.2022.01.450>
- Black, J. T., & Kosher, R. A. (2012). *DeGarmo's Materials and Processes In Manufacturing*. John Wiley & Sons, Inc.
- Buldum, B., Eşme, U., Külekci, M. K., Şik, A., & Kazançoğlu, Y. (2012). Use of grey-taguchi method for the optimization of oblique turning process of AZ91D magnesium alloy. *Materialpruefung/Materials Testing*, 54(11–12), 779–785. <https://doi.org/10.3139/120.110392>
- Cabanettes, F., Cherguy, O., Courbon, C., Giovenco, A., Han, S., & Rech, J. (2020). Towards the prediction of surface roughness induced by the belt finishing process: Influence of the workmaterial on the roughness reduction rate. *Procedia CIRP*, 87, 210–215. <https://doi.org/10.1016/j.procir.2020.02.108>
- Christensen, R. (2016). *Analysis of Variance, Design, and Regression Linear Modeling for Unbalanced Data* (Second Edition). CRC Press.
- Ekambaram, S., & Murugan, N. (2015). Synthesis and Characterization of Aluminium Alloy AA6061-Alumina Metal Matrix Composite International Journal of Current Engineering and Technology Synthesis and Characterization of Aluminium Alloy AA6061-Alumina Metal Matrix Composite. In *Article in International Journal of Engineering and*

- Technology* (Vol. 5, Issue 5). <http://inpressco.com/category/ijcet>
- Groover, M. P. (2010). *Fundamentals of Modern Manufacturing* (4th Edition). John Wiley & Sons, Inc.
- Harell, C. R., Ghosh, B. K., & Bowden, R. O. (2012). *Simulation Using ProModel*. McGraw-Hill.
- Javidikia, M., Sadeghifar, M., Songmene, V., & Jahazi, M. (2020). Analysis and optimization of surface roughness in turning of AA6061-T6 under various environments and parameters. *Procedia CIRP*, 101, 17–20. <https://doi.org/10.1016/j.procir.2021.02.004>
- Kandi, R., Sahoo, S. K., & Sahoo, A. K. (2020). Ultrasonic vibration-assisted turning of Titanium alloy Ti–6Al–4V: numerical and experimental investigations. *Journal of the Brazilian Society of Mechanical Sciences and Engineering*, 42(8). <https://doi.org/10.1007/s40430-020-02481-5>
- Kaufman, J. G. (John G. (2008). *Properties of aluminum alloys : fatigue data and the effects of temperature, product form, and processing*. ASM International.
- Kumar, R., Sahoo, A. K., Das, R. K., Panda, A., & Mishra, P. C. (2018). Modelling of Flank wear, Surface roughness and Cutting Temperature in Sustainable Hard Turning of AISI D2 Steel. *Procedia Manufacturing*, 20, 406–413. <https://doi.org/10.1016/j.promfg.2018.02.059>
- Mitsubishi Materials Corporation. (2022). *Formula for Turning*. [http://www.mitsubishicarbide.com/en/technical\\_information/tec\\_turning\\_tools/tec\\_turning\\_insert/tec\\_turning\\_formula/tec\\_turning\\_formula#](http://www.mitsubishicarbide.com/en/technical_information/tec_turning_tools/tec_turning_insert/tec_turning_formula/tec_turning_formula#)
- Myers, R. H., Montgomery, D. C., & Anderson-Cook, C. M. (2016). *Response Surface Methodology: Process and Product Optimization Using Designed Experiments* (4th Edition). John Wiley & Sons, Inc.
- Nayak, N. K., & Sodhi, H. S. (2017). Optimization of CNC turning parameters for al-6061 using response surface methodology. *International Journal of Mechanical and Production Engineering Research and Development*, 7(4), 127–138. <https://doi.org/10.24247/ijmperdaug201714>
- Nordgren, A., Samani, B. Z., & MSAoubic, R. (2014). Experimental study and modelling of plastic deformation of cemented carbide tools in turning.

- Procedia CIRP*, 14, 599–604. <https://doi.org/10.1016/j.procir.2014.03.021>
- Qehaja, N., Jakupi, K., Bunjaku, A., Bruçi, M., & Osmani, H. (2015). Effect of machining parameters and machining time on surface roughness in dry turning process. *Procedia Engineering*, 100(January), 135–140. <https://doi.org/10.1016/j.proeng.2015.01.351>
- Rafidah, A., Nurulhuda, A., Azrina, A., Suhaila, Y., Anwar, I. S., & Syafiq, R. A. (2014). Comparison design of experiment (DOE): Taguchi method and full factorial design in surface roughness. *Applied Mechanics and Materials*, 660, 275–279. <https://doi.org/10.4028/www.scientific.net/AMM.660.275>
- Rao, C. J., Rao, D. N., & Srihari, P. (2013). Influence of cutting parameters on cutting force and surface finish in turning operation. *Procedia Engineering*, 64, 1405–1415. <https://doi.org/10.1016/j.proeng.2013.09.222>
- Saravanakumar, A., Karthikeyan, S. C., Dhamotharan, B., & Kumar, V. G. (2018). Optimization of CNC Turning Parameters on Aluminum Alloy 6063 using Taguchi Robust Design. *Materials Today: Proceedings*, 5(2), 8290–8298. <https://doi.org/10.1016/j.matpr.2017.11.520>
- Shah, D., & Bhavsar, S. (2020). Effect of Tool Nose Radius and Machining Parameters on Cutting Force, Cutting Temperature and Surface Roughness- An Experimental Study of Ti-6Al-4V (ELI). In *D. Shah and S. Bhavsar / Materials Today: Proceedings* (Vol. 22). [www.sciencedirect.com/www.materialstoday.com/proceedings2214-7853](http://www.sciencedirect.com/www.materialstoday.com/proceedings2214-7853)
- Srivastava, V. S., Gupta, T. K., Srivastava, A. K., Chauhan, S., & Chauhan, P. K. (2021). Effects of cutting parameters on aluminium alloys-A review. *Materials Today: Proceedings*, 47, 3823–3827. <https://doi.org/10.1016/j.matpr.2021.03.091>
- Veera Ajay, C., & Vinoth, V. (2019). Optimization of process parameters in turning of aluminum alloy using response surface methodology. *Materials Today: Proceedings*, 46, 9462–9468. <https://doi.org/10.1016/j.matpr.2020.03.236>
- Velan, M. V. G. V., Subha Shree, M., & Muthuswamy, P. (2020). Effect of cutting parameters and high-pressure coolant on forces, surface roughness

- and tool life in turning AISI 1045 steel. *Materials Today: Proceedings*, 43, 482–489. <https://doi.org/10.1016/j.matpr.2020.12.020>
- Vivekananda, K., Arka, G. N., & Sahoo, S. K. (2014). Design and analysis of ultrasonic vibratory tool (UVT) using FEM, and experimental study on Ultrasonic Vibration-assisted turning (UAT). *Procedia Engineering*, 97, 1178–1186. <https://doi.org/10.1016/j.proeng.2014.12.396>
- Yang, Z., Zhu, L., Zhang, G., Ni, C., & Lin, B. (2020). Review of ultrasonic vibration-assisted machining in advanced materials. In *International Journal of Machine Tools and Manufacture* (Vol. 156). Elsevier Ltd. <https://doi.org/10.1016/j.ijmachtools.2020.103594>
- Yousefi, S., & Zohoor, M. (2018). Experimental Studying of the Variations of Surface Roughness and Dimensional Accuracy in Dry Hard Turning Operation. *The Open Mechanical Engineering Journal*, 12(1), 175–191. <https://doi.org/10.2174/1874155x01812010175>
- Zhang, P., Zhang, X., Cao, X., Yu, X., & Wang, Y. (2021). Analysis on the tool wear behavior of 7050-T7451 aluminum alloy under ultrasonic elliptical vibration cutting. *Wear*, 466–467. <https://doi.org/10.1016/j.wear.2020.203538>
- Zou, P., Xu, Y., He, Y., Chen, M., & Wu, H. (2015). Experimental investigation of ultrasonic vibration assisted turning of 304 austenitic stainless steel. *Shock and Vibration*, 2015. <https://doi.org/10.1155/2015/817598>