

REFERENCES

- [1] Y. Ichikawa dan N. Ozaki, *Introduction to Autonomous Mobile Robot*, 1 ed. London, England: The MIT Press, 2004.
- [2] E. B. Utomo, “Autonomous Mobile Robot Berbasis Landmark Menggunakan Particle Filter Dan Occupancy Grid Maps Untuk Navigasi , Landmark Using Particle Filter and Occupancy Grid Maps for Navigation , Localization , and Mapping,” INSTITUT TEKNOLOGI SEPULUH NOPEMBER, 2015.
- [3] A. Thirugnanam, J. Zeng, dan K. Sreenath, “A Fast Computational Optimization for Optimal Control and Trajectory Planning for Obstacle Avoidance between Polytopes.”
- [4] I. Doroftei, V. Grosu, dan V. Spinu, “Design and control of an omni-directional mobile robot,” *Nov. Algorithms Tech. Telecommun. Autom. Ind. Electron.*, hal. 105–110, 2008, doi: 10.1007/978-1-4020-8737-0_19.
- [5] M. Z. Romdlony dan B. Jayawardhana, “Stabilization with guaranteed safety using Control Lyapunov-Barrier Function,” *Automatica*, vol. 66, hal. 39–47, 2016, doi: 10.1016/j.automatica.2015.12.011.
- [6] J. Lygeros, K. H. Johansson, S. N. Simić, J. Zhang, dan S. S. Sastry, “Dynamical properties of hybrid automata,” *IEEE Trans. Automat. Contr.*, vol. 48, no. 1, hal. 2–17, 2003, doi: 10.1109/TAC.2002.806650.
- [7] Q. Zhang, “Combination Strategy of Dynamic Obstacle- Avoidance and Autonomous Tracking for Hazardous Gases Inspection Robot in Man-Machine Environment,” 2021.
- [8] M. R. Azizi dan A. Rastegarpanah, “Motion Planning and Control of an Omnidirectional Mobile,” hal. 1–27, 2021, doi: <https://doi.org/10.3390/robotics10010048>.

- [9] S. G. Tzafestas, *Introduction to Mobile Robot Control*. 2013.
- [10] D. S. Roland Siegwart, Illah Reza Nourbakhsh, *Autonomous Mobile Robots*, vol. 2. London, England: A Bradford Book, 2011.
- [11] I. Zeidis dan K. Zimmermann, “Dynamics of a Four-Wheeled Mobile Robot with Mecanum Wheels,” *ZAMM Zeitschrift für Angew. Math. und Mech.*, vol. 99, no. 12, hal. 1–22, 2019, doi: 10.1002/zamm.201900173.
- [12] M. Y. Naing, A. S. Oo, I. Nilkhamhang, dan T. Than, “Development of Computer Vision-Based Movement Controlling in Mecanum Wheel Robotic Car,” *2019 1st Int. Symp. Instrumentation, Control. Artif. Intell. Robot. ICA-SYMP 2019*, hal. 45–48, 2019, doi: 10.1109/ICA-SYMP.2019.8646254.
- [13] Z. Hendzel dan Ł. Ł. A. Ryka, “MODELLING OF DYNAMICS OF A WHEELED MOBILE ROBOT WITH MECANUM WHEELS WITH THE USE OF LAGRANGE EQUATIONS OF THE SECOND KIND,” vol. 22, no. 1, hal. 81–99, 2017, doi: 10.1515/ijame-2017-0005.
- [14] A. N. Michel, “Lyapunov Methods,” *Wiley Encycl. Electr. Electron. Eng.*, 1999, doi: 10.1002/047134608x.w2434.
- [15] K. S. Candan dan A. Celentano, *Hybrid Systems: Computation and Control*, vol. 3665 LNCS. San Francisco: Srpinger, 2009.
- [16] Eric, “Explanation of Latitude and Longitude,” *Satellite Signals*, 2021. https://www.satsig.net/lat_long.htm (diakses Nov 18, 2021).
- [17] S. P. Drake, “Converting GPS Coordinates (longitude, latitude, h) to Navigation Coordinates (ENU),” *DSTO Electron. Surveill. Res. Lab.*, 2002, [Daring]. Tersedia pada: <https://www.researchgate.net/publication/27253833> Converting.