# BIBLIOGRAPHY


[1] Z. K. A. Baizal, D. H. Widyantoro, and N. Ulfa, "Data & Knowledge Engineering Computational model for generating interactions in conversational recommender system based on product functional requirements," *Data Knowl. Eng.*, vol. 128, no. March, p. 101813, 2020, doi: 10.1016/j.datak.2020.101813.

[2] Z. K. . Baizal, N. U. Maulidevi, and D. H. Widyantoro, *Conversational Recommender System Berbassi Pada Kebutuhan Fungsional Produk*. Informatika Bandung, 2019.

[3] W. Lei *et al.*, "Interactive Path Reasoning on Graph for Conversational Recommendation," *Proc. ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, pp. 2073–2083, 2020, doi: 10.1145/3394486.3403258.

[4] M. Sadeghian, M. S. Student, and M. Khansari, "A Recommender Systems Based on Similarity Networks: MovieLens Case Study," 2018. [Online]. Available: http://grouplens.org/datasets/movielens/.

[5] D. H. Widyantoro and Z. K. A. Baizal, "A framework of conversational recommender system based on user functional requirements," *2014 2nd Int. Conf. Inf. Commun. Technol. ICoICT 2014*, pp. 160–165, 2014, doi: 10.1109/ICoICT.2014.6914058.

[6] Z. K. A. Baizal, H. Widyantoro, and U. Maulidevi, "Design of Knowledge for Conversational Recommender System Based on Product Functional Requirements," 2016.

[7] Z. K. A. Baizal, D. H. Widyantoro, and N. U. Maulidevi, "Query Refinement in Recommender System Based on Product Functional Requirements," pp. 2–7.

[8] Z. K. A. Baizal, D. Tarwidi, and B. Wijaya, "Tourism Destination Recommendation Using Ontology-based Conversational Recommender System," vol. 1, no. 1, 2021.

[9] P. Mertens, "Recommender Systems," *Wirtschaftsinformatik*, vol. 39, no. 4, pp. 401–404, 1997.

[10] S. Zhang, L. Yao, A. Sun, and Y. I. Tay, “Deep Learning Based Recommender System : A Survey,” vol. 52, no. 1, 2019.

[11] A. M. G. Harvey and R. J. Johns, *Recommender Systems Handbook*, vol. 32, no. 1. 1962.

[12] D. Theosaksomo and D. H. Widyantoro, “Conversational Recommender System Chatbot Based on Functional Requirement,” pp. 154–159.

[13] K. Christakopoulou, F. Radlinski, and K. Hofmann, “Towards Conversational Recommender Systems,” no. 3, pp. 815–824.

[14] D. Pramod and P. Bafna, “Conversational recommender systems techniques, tools, acceptance, and adoption: A state of the art review,” *Expert Systems with Applications*, vol. 203. Elsevier Ltd, Oct. 01, 2022, doi: 10.1016/j.eswa.2022.117539.

[15] N. Guarino, “Ontologies and Knowledge Bases.”

[16] A. Klašnja-milic, “Expert Systems with Applications Protus 2 . 0 : Ontology-based semantic recommendation in programming tutoring system,” vol. 39, pp. 12229–12246, 2012, doi: 10.1016/j.eswa.2012.04.052.

[17] D. Lee and K. Hosanagar, “How do recommender systems affect sales diversity? A cross-category investigation via randomized field experiment,” *Inf. Syst. Res.*, vol. 30, no. 1, pp. 239–259, 2019, doi: 10.1287/isre.2018.0800.

[18] Yehuda Koren, “MATRIX FACTORIZATION TECHNIQUES FOR RECOMMENDER SYSTEMS,” 2009.

[19] Y. Chen, S. Mensah, F. Ma, H. Wang, and Z. Jiang, “Collaborative filtering grounded on knowledge graphs,” *Pattern Recognit. Lett.*, vol. 151, pp. 55–61, Nov. 2021, doi: 10.1016/j.patrec.2021.07.022.

[20] X. Ning, C. Desrosiers, and G. Karypis, “A comprehensive survey of neighborhood-based recommendation methods,” in *Recommender Systems Handbook, Second Edition*, Springer US, 2015, pp. 37–76.

[21] T. Web-based, “Helping Online Customers Decide through Web Personalization,” 2002.

[22] V. Subramaniyaswamy, R. Logesh, M. Chandrashekhar, A. Challa, and V. Vijayakumar, “A personalised movie recommendation system based on collaborative filtering,” *Int. J. High Perform. Comput. Netw.*, vol. 10, no. 1–2, pp. 54–63, 2017, doi: 10.1504/IJHPCN.2017.083199.

[23] B.-B. Cui, “Design and Implementation of Movie Recommendation System Based on Knn Collaborative Filtering Algorithm,” *ITM Web Conf.*, vol. 12, p. 04008, 2017, doi: 10.1051/itmconf/20171204008.

[24] X. Zhou, J. He, G. Huang, and Y. Zhang, “SVD-based incremental approaches for recommender systems,” *J. Comput. Syst. Sci.*, vol. 81, no. 4, pp. 717–733, 2015, doi: 10.1016/j.jcss.2014.11.016.

[25] J. Jiao, X. Zhang, F. Li, and Y. Wang, “A Novel Learning Rate Function and Its Application on the SVD++ Recommendation Algorithm,” *IEEE Access*, vol. 8, pp. 14112–14122, 2020, doi: 10.1109/ACCESS.2019.2960523.

[26] N. Bhatia and Vandana, “Survey of Nearest Neighbor Techniques,” vol. 8, no. 2, pp. 302–305, 2010, [Online]. Available: http://arxiv.org/abs/1007.0085.

[27] S. F. Hafshejani and Z. Moaberfard, “Initialization for Nonnegative Matrix Factorization: a Comprehensive Review,” no. 1, pp. 1–19, 2021, [Online]. Available: http://arxiv.org/abs/2109.03874.

[28] T. Anwar, V. Uma, M. I. Hussain, and M. Pantula, “Collaborative filtering and kNN based recommendation to overcome cold start and sparsity issues: A comparative analysis,” *Multimed. Tools Appl.*, no. March, 2022, doi: 10.1007/s11042-021-11883-z.

[29] C. Res, C. J. Willmott, and K. Matsuura, “Advantages of the mean absolute error ( MAE ) over the root mean square error ( RMSE ) in assessing average model performance,” vol. 30, pp. 79–82, 2005.

[30] C. J. Willmott, K. Matsuura, and S. M. Robeson, "Ambiguities inherent in sums-of-squares-based error statistics," *Atmos. Environ.*, vol. 43, no. 3, pp. 749–752, 2009, doi: 10.1016/j.atmosenv.2008.10.005.