

BIBLIOGRAPHY

- [1] X. Zhu and A. B. Goldberg, “Introduction to semi-supervised learning,” *Synthesis lectures on artificial intelligence and machine learning*, vol. 3, no. 1, pp. 1–130, 2009.
- [2] T. O. Ayodele, “Types of machine learning algorithms,” *New advances in machine learning*, vol. 3, pp. 19–48, 2010.
- [3] M. C. Du Plessis and M. Sugiyama, “Semi-supervised learning of class balance under class-prior change by distribution matching,” *Neural Networks*, vol. 50, pp. 110–119, 2014.
- [4] T. Zhang, T. Zhu, J. Li, M. Han, W. Zhou, and P. S. Yu, “Fairness in semi-supervised learning: Unlabeled data help to reduce discrimination,” *IEEE Transactions on Knowledge and Data Engineering*, vol. 34, no. 4, pp. 1763–1774, 2022.
- [5] E. Arazo, D. Ortego, P. Albert, N. E. O’Connor, and K. McGuinness, “Pseudo-labeling and confirmation bias in deep semi-supervised learning,” in *2020 International Joint Conference on Neural Networks (IJCNN)*, 2020, pp. 1–8.
- [6] Y. Yang and Z. Xu, “Rethinking the value of labels for improving class-imbalanced learning,” *Advances in Neural Information Processing Systems*, vol. 33, pp. 19 290–19 301, 2020.
- [7] M. Hyun, J. Jeong, and N. Kwak, “Class-imbalanced semi-supervised learning,” 2020. [Online]. Available: <https://arxiv.org/abs/2002.06815>
- [8] C. Wei, K. Sohn, C. Mellina, A. L. Yuille, and F. Yang, “Crest: A class-rebalancing self-training framework for imbalanced semi-supervised learning,” *CoRR*, vol. abs/2102.09559, 2021. [Online]. Available: <https://arxiv.org/abs/2102.09559>
- [9] O. Chapelle, B. Schölkopf, and A. Zien, “Semi-supervised learning,” *MIT press*, 2010.
- [10] S.-w. Lee and S.-w. Whang, “Pseudo-label: The simple and efficient semi-supervised learning method,” *arXiv preprint arXiv:1306.4185*, 2013.

- [11] S. Laine and T. Aila, “Temporal ensembling for semi-supervised learning,” *arXiv preprint arXiv:1610.02242*, 2016.
- [12] D. Berthelot, T. Schumm, L. Metz, B. Poole, C. Alexander, and A. v. d. Oord, “Mixmatch: A holistic approach to semi-supervised learning,” in *International Conference on Learning Representations*, 2019.
- [13] K. Sohn, R. Roelofs, B. Zoph, Q. V. Le, and J. Shlens, “Fixmatch: Simplify-ing semi-supervised learning with consistency and confidence,” *arXiv preprint arXiv:2001.07685*, 2020.
- [14] L. Breiman, “Random forests,” *Machine learning*, vol. 45, no. 1, pp. 5–32, 2001.
- [15] J. H. Friedman, “Greedy function approximation: a gradient boosting machine,” *Annals of statistics*, pp. 1189–1232, 2001.
- [16] R. Kohavi, “A study of cross-validation and bootstrap for accuracy estimation and model selection,” *International joint conference on artificial intelligence*, pp. 1137–1143, 1995.
- [17] B. Efron, *An introduction to the bootstrap*. Chapman and Hall/CRC, 1994.
- [18] C. Rosenberg, M. Hebert, and H. Schneiderman, “Semi-supervised self-training of object detection models,” 2005.
- [19] L. Taylor and G. Nitschke, “Improving deep learning with generic data augmentation,” in *2018 IEEE Symposium Series on Computational Intelligence (SSCI)*. IEEE, 2018, pp. 1542–1547.
- [20] Y. Balaji, H. Hassani, R. Chellappa, and S. Feizi, “Entropic gans meet vaes: A statistical approach to compute sample likelihoods in gans,” in *International Conference on Machine Learning*. PMLR, 2019, pp. 414–423.
- [21] J. Davis and M. Goadrich, “The relationship between precision-recall and roc curves,” in *Proceedings of the 23rd International Conference on Machine Learning*, ser. ICML ’06. New York, NY, USA: Association for Computing Machinery, 2006, p. 233–240. [Online]. Available: <https://doi.org/10.1145/1143844.1143874>
- [22] E. Bauer and R. Kohavi, “A survey of dataset shift in machine learning,” *The Journal of Machine Learning Research*, vol. 8, pp. 1825–1832, 2007.

- [23] A. Krizhevsky, G. Hinton *et al.*, “Learning multiple layers of features from tiny images,” 2009.
- [24] T. Wu, X. Wang, Q. Ye, and Y. Liu, “Long-tailed recognition in large-scale datasets,” *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 816–833, 2018.
- [25] E. Bisong and E. Bisong, “Google colab,” *Building machine learning and deep learning models on google cloud platform: a comprehensive guide for beginners*, pp. 59–64, 2019.
- [26] S. Zagoruyko and N. Komodakis, “Wide residual networks,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2016, pp. 778–786.
- [27] S. Ioffe and C. Szegedy, “Batch normalization: Accelerating deep network training by reducing internal covariate shift,” *arXiv preprint arXiv:1502.03167*, 2015.
- [28] A. L. Maas, A. Y. Hannun, and A. Y. Ng, “Rectifier nonlinearities improve neural network acoustic models,” *Proc. ICML*, vol. 30, p. 3, 2013.
- [29] Z. Zhou, L. Chen, J. Sun, and X. Wang, “Deep class rebalancing for long-tailed recognition,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.
- [30] S. Zhang, Z. Zhou, L. Chen, M. Gong, and X. Wang, “Range loss for deep face recognition with long-tailed training data,” *arXiv preprint arXiv:1711.09349*, 2017.