Daftar Pustaka

[1] N. Alsaaran and M. Alrabiah. Classical arabic named entity recognition using variant deep neural network architectures and BERT. *IEEE Access*, 9:91537–91547, 2021.

[2] F. D. Arvianto, M. A. Bijaksana, and A. F. Huda. People entity recognition in indonesian quran translation with conditional random field approach. In *2019 7th International Conference on Information and Communication Technology (ICoICT)*, pages 1–5. IEEE, 2019.

[3] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[4] R. Grishman and B. M. Sundheim. Message understanding conference-6: A brief history. In *COLING 1996 Volume 1: The 16th International Conference on Computational Linguistics*, 1996.

[5] J. Han, M. Kamber, and J. Pei. 8 - classification: Basic concepts. In J. Han, M. Kamber, and J. Pei, editors, *Data Mining (Third Edition)*, The Morgan Kaufmann Series in Data Management Systems, pages 327–391. Morgan Kaufmann, Boston, third edition edition, 2012.

[6] Z. Huang, W. Xu, and K. Yu. Bidirectional lstm-crf models for sequence tagging. *arXiv preprint arXiv:1508.01991*, 2015.

[7] C. Khaeroni. Sejarah al-qur'an (uraian analitis, kronologis, dan naratif tentang sejarah kodifikasi al-qur'an). 5:193–206, 2017.

[8] N. Kitaev and D. Klein. Constituency parsing with a self-attentive encoder. *arXiv preprint arXiv:1805.01052*, 2018.

[9] K. Kurniawan and A. F. Aji. Toward a standardized and more accurate indonesian part-of-speech tagging. In *2018 International Conference on Asian Language Processing (IALP)*, page 303–307. IEEE, Nov 2018. arXiv: 1809.03391.

[10] J. Lafferty, A. McCallum, and F. C. Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. 2001.

[11] M. A. Maulana, M. A. Bijaksana, and A. F. Huda. Entity recognition for quran english version with supervised learning approach. *Indonesian Journal on Computing (Indo-JC)*, 4(3):77–86, 2019.

[12] A. McCallum, D. Freitag, and F. C. Pereira. Maximum entropy markov models for information extraction and segmentation. In *Icml*, volume 17, pages 591–598, 2000.

[13] D. Nadeau and S. Sekine. A survey of named entity recognition and classification. *Lingvisticae Investigationes*, 30(1):3–26, 2007.

[14] S. H. Nasr, C. K. Dagli, M. M. Dakake, J. E. Lumbard, and M. Rustom. The study quran. *A new translation and commentary*, 19, 2015.

[15] N. Plath, M. Toussaint, and S. Nakajima. Multi-class image segmentation using conditional random fields and global classification. In *Proceedings of the 26th Annual International Conference on Machine Learning*, pages 817–824, 2009.

[16] L. A. Ramshaw and M. P. Marcus. Text chunking using transformation-based learning. In *Natural language processing using very large corpora*, pages 157–176. Springer, 1999.

[17] E. F. Sang and S. Buchholz. Introduction to the conll-2000 shared task: Chunking. *arXiv preprint cs/0009008*, 2000.

[18] E. F. Sang and J. Veenstra. Representing text chunks. *arXiv preprint cs/9907006*, 1999.

[19] B. Settles. Biomedical named entity recognition using conditional random fields and rich feature sets. In *Proceedings of the international joint workshop on natural language processing in biomedicine and its applications (NLPBA/BioNLP)*, pages 107–110, 2004.

[20] K. Shaalan and H. Raza. NERA: Named entity recognition for arabic. *J. Am. Soc. Inf. Sci. Technol.*, 60(8):1652–1663, Aug. 2009.

[21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, . Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.

[22] D. C. Wintaka, M. A. Bijaksana, and I. Asror. Named-entity recognition on indonesian tweets using bidirectional lstm-crf. *Procedia Computer Science*, 157:221–228, 2019.

[23] V. Yadav and S. Bethard. A survey on recent advances in named entity recognition from deep learning models. *arXiv preprint arXiv:1910.11470*, 2019.