

LIST OF PICTURE

Figure 2.1 Work System and Mechanism of Through the Wall Radar wave propagation.....	5
Figure 2.2 Illustration of the Rx signal	7
Figure 2.3 Signal reconstruction.....	7
Figure 2.4 Delay estimation modeling method	9
Figure 2.5 S-parameter VNA	11
Figure 2. 6 Pemodelan Radar TWR menggunakan VNA.....	13
Figure 3.1 Deconvolution Method.....	19
Figure 3.2 Delay Estimation Method.....	20
Figure 3.3 Signal Reconstruction	21
Figure 3.4 Modeling Through the Wall Radar System (Free loss)	21
Figure 3.5 Modeling of Through the Wall Radar System with barrier walls	22
Figure 3.6 TWR Modeling with Barrier Walls and Objects	22
Figure 4.1 Signals Received without walls and objects.....	24
Figure 4.2 Monocycle Signal (Ideal Signal)	25
Figure 4.3 Proving the Location of the Barrier Wall Signal	26
Figure 4.4 Laboratorium Experiments of One-Layer Light Brick Wall	27
Figure 4.5 Wall Effect Signal one layer Light Brick Wall	28
Figure 4.6 The Two-Layers light Brick Wall Laboratory Experiment	29
Figure 4.7 Signals of a 2-layer light brick wall.....	30
Figure 4.8 One-layer plywood wall lab experiment	31
Figure 4.9 Signals of the Effect of the 1 Layer Plywood Wall	32
Figure 4.10 The two-layer plywood wall laboratory experiment.....	33
Figure 4. 11 Signals of the Effect of the two-layers Plywood Wall	34
Figure 4. 12 Illustration of Object Shift	35
Figure 4. 13 Realization of taking the effect of a one-layer light brick wall using an object	36

Figure 4. 14 testing a single layer light brick wall with an object 30 cm in front of the wall	37
Figure 4. 15 the position of the object behind the wall with a distance of 30 cm.....	38
Figure 4.16 Object point validation using thresholding.....	39
Figure 4. 17 Object position behind a light brick wall at a distance of 40 cm.....	40
Figure 4. 18 Validation point object distance 40 cm	41
Figure 4. 19 B-Scan of Object Point Location	42
Figure 4. 20 Object validation distance 50 cm.....	43
Figure 4. 21 the position of the object is reversed behind a single layer of lightweight brick wall at a distance of 60 cm.....	44
Figure 4. 22 Object point validation 60 cm.....	45
Figure 4. 23 Object position behind a single layer light brick wall with a distance of 70 cm	46
Figure 4. 24 Object Validation using 70 cm	47
Figure 4. 25 Object position behind a single layer wall at a distance of 80 cm	48
Figure 4. 26 Realization of signal retrieval of the effect of two-layer light brick walls using objects	49
Figure 4. 27 the position of the object behind a two-layer light brick wall 30 cm.....	50
Figure 4. 28 Validation of object distance of 30 cm on 2 layers of light brick wall.....	51
Figure 4. 29 the position of the object behind a two-layer light brick wall 40 cm.....	52
Figure 4. 30 Validasi titik objek jarak 40 cm pada bata ringan dua lapis	53
Figure 4. 31 B-Scan of Object Point Location	54
Figure 4. 32 Validation of 50 cm distance object points on 2 layers light brick wall.....	55
Figure 4.33 the position of the object behind the wall with a distance of 60 cm	56

Figure 4. 34 Validation of 60 cm distance object points on 2 layers of light brick wall.....	57
Figure 4.35 The position of the object behind the wall with a distance of 70 cm.....	58
Figure 4. 36 Validation of 70 cm object point on 2 layers light brick wall	59
Figure 4. 37 the position of the object behind the wall with a distance of 80 cm.....	60
Figure 4. 38 Object position behind the plywood wall with a distance of 30 cm.....	61
Figure 4. 39 Validation of 30 cm distance objects on one layer plywood.....	62
Figure 4. 40 Object position behind the plywood wall with a distance of 40 cm.....	63
Figure 4. 41 Validation of 40 cm distance objects on single-layer plywood.....	64
Figure 4. 42 B-Scan of Object Point Location	65
Figure 4. 43 Validation of 50 cm distance objects on single-layer plywood.....	66
Figure 4. 44 Object position behind the wall with a distance of 60 cm.....	67
Figure 4. 45 Validation of 60 cm object on single layer plywood	68
Figure 4. 46 Object position behind the wall with a distance of 70 cm.....	69
Figure 4. 47 Validation of object distance 70 cm on single layer plywood.....	70
Figure 4. 48 the position of the object behind the wall with a distance of 80 cm.....	71
Figure 4. 49 Validation of 80 cm object on single layer plywood	72
Figure 4. 50 Realization of taking the effect of two-layer plywood wall using an object	73
Figure 4. 51 the position of the object behind the wall of two layers with a distance of 30 cm	74
Figure 4. 52 Validation of 30 cm objects on two-layer plywood.....	75
Figure 4. 53 the position of the object behind the wall of two layers with a distance of 40 cm	76
Figure 4. 54 Validation of 40 cm distance objects on two-layer plywood	77

Figure 4. 55 B-Scan of Object Point Location	78
Figure 4. 56 Validation of 50 cm distance objects on two-layer plywood	79
Figure 4.57 the position of the object behind the wall of two layers with a distance of 60 cm	80
Figure 4. 58 Validation of 60 cm distance objects on two-layer plywood	81
Figure 4. 59 the position of the object behind the wall of two layers with a distance of 60 cm	82
Figure 4. 60 Validation of object distance 70 cm on two-ply plywood.....	83
Figure 4. 61 the position of the object behind a 2-layer plywood wall with a distance of 80 cm	84
Figure 4. 62 Validate 80 cm distance object on two-layer plywood	85
Figure 4. 63 the result of the reconstruction signal	86
Figure 4. 64 the B-Scan Results	87
Figure 4.65 The Object's Validation Point	88
Figure 4.66 Barrier wall point validation	88
Figure 4.67 the B-Scan Results	90
Figure 4.68 The Object's Validation Point	91
Figure 4.69 Barrier wall point validation	91
Figure 4. 70 The B-Scan Results	93
Figure 4.71 The Object's Validation Point	93
Figure 4. 72 Barrier wall point validation	94
Figure 4.73 The B-Scan Results	95
Figure 4.74 The Object's Validation Point	96
Figure 4.75 Barrier wall point validation	96
Figure 4.76 The B-Scan Results	97
Figure 4.77 The Object's Validation Point	98
Figure 4.78 Barrier wall point validation	99
Figure 4.79 The B-Scan Results	100
Figure 4.80 The Object's Validation Point	101
Figure 4.81 Barrier wall point validation	101

Figure 4.82 the B-Scan Results	102
Figure 4.83 The Object's Validation Point	103
Figure 4.84 Barrier wall point validation	104
Figure 4.85 The B-Scan Results	105
Figure 4.86 The Object's Validation Point	105
Figure 4.87 Barrier wall point validation	106
Figure 4. 88 Results of a Brick Wall Reconstruction Signal Using An Object With A Distance of 50 Cm	107
Figure 4. 89 B-Scan Data Set	108
Figure 4.90 The Object's Validation Point	108
Figure 4.91 Barrier wall point validation	109
Figure 4.92 The B-Scan Results	110
Figure 4.93 The Object's Validation Point	111
Figure 4.94 Barrier wall point validation	111
Figure 4.95 the B-Scan Results	112
Figure 4.96 The Object's Validation Point	113
Figure 4.97 Barrier wall point validation	113
Figure 4.98 the B-Scan Results	114
Figure 4.99 The Object's Validation Point	115
Figure 4.100 Barrier wall point validation	116
Figure 4.101 the B-Scan Results	117
Figure 4.102 The Object's Validation Point	118
Figure 4.103 Barrier wall point validation	118
Figure 4.104 the B-Scan Results	119
Figure 4.105 The Object's Validation Point	120
Figure 4.106 Barrier wall point validation	121
Figure 4. 107 Results of a One-Layer Plywood Reconstruction Signal Using An Object With A Distance of 50 Cm	122
Figure 4.108 B-scan the data set.....	123
Figure 4.109 The Object's Validation Point	124

Figure 4.110 Barrier wall point validation	124
Figure 4. 111 the B-Scan Results	125
Figure 4.112 The Object's Validation Point	126
Figure 4.113 Barrier wall point validation	126
Figure 4.114 the B-Scan Results	127
Figure 4.115 The Object's Validation Point	128
Figure 4.116 Barrier wall point validation	129
Figure 4.117 the B-Scan Results	130
Figure 4. 118 The Object's Validation Point	130
Figure 4.119 Barrier wall point validation	131
Figure 4.120 The B-Scan Result.....	132
Figure 4.121 The Object's Validation Point	132
Figure 4.122 Barrier wall point validation	133
Figure 4.123 the B-Scan Result.....	134
Figure 4.124 The Object's Validation Point	134
Figure 4.125 Barrier wall point validation	135
Figure 4.126 Results of a two-layer plywood reconstruction signal using an object with a distance of 50 cm	136
Figure 4.127 B-scan the data set.....	137
Figure 4.128 the object's validation point	137
Figure 4.129 Barrier Wall Point Validation	138
Figure 4.130 the B-Scan Results	139
Figure 4.131 The Object's Validation Point	140
Figure 4.132 Barrier wall point validation	140
Figure 4.133 the B-Scan Results	141
Figure 4.134 The Object's Validation Point	142
Figure 4.135 Barrier wall point validation	143
Figure 4.136 the B-Scan Results	144
Figure 4.137 The Object's Validation Point	144
Figure 4.138 Barrier wall point validation	145

Figure 7. 1 A-scan single layer light brick (40 cm) 168