

DAFTAR SINGKATAN

| | |
|-----|---|
| °C | : <i>Celcius</i> |
| 3R | : <i>Reuse, Reduce, Recycle</i> |
| AC | : <i>Alternating Current</i> |
| BPS | : <i>Bits Per Second</i> |
| CD | : <i>Capstone Design</i> |
| DC | : <i>Direct Current</i> |
| DLP | : <i>Digital Light Processing</i> |
| DO | : <i>Digital Output</i> |
| FDM | : <i>Fused Deposition Modeling</i> |
| GND | : <i>Ground</i> |
| I/O | : <i>Input/Output</i> |
| IC | : <i>Integrated Circuit</i> |
| IoT | : <i>Internet of Things</i> |
| LCD | : <i>Liquid Crystal Display</i> |
| NTC | : <i>Negative Temperature Coefficient</i> |
| mm | : <i>Milimeter</i> |
| Pbb | : <i>Pembimbing</i> |
| PET | : <i>Polyethylene Terephthalate</i> |
| PNP | : <i>Positive-Negative-Positive</i> |
| RPM | : <i>Revolutions Per Minute</i> |
| SLA | : <i>Stereolithography</i> |
| SLS | : <i>Selective Laser Sintering</i> |
| STA | : <i>Sidang Tugas Akhir</i> |
| THD | : <i>Total Harmonic Distortion</i> |
| UKM | : <i>Usaha Kecil dan Menengah</i> |
| USB | : <i>Universal Serial Bus</i> |
| VCC | : <i>Voltage Common Collector</i> |