

---

## LIST OF FIGURES

1.1	Research Methodology . . . . .	4
1.2	Communication Design of Grid . . . . .	5
2.1	Hourglass IP-NDN Architecture . . . . .	6
2.2	Flow of NDN Communication . . . . .	7
2.3	CS, PIT & FIB Structure . . . . .	7
2.4	NFD Modules . . . . .	9
2.5	Forwarding Workflow . . . . .	10
2.6	Traditional vs Modern Grid System . . . . .	11
2.7	Classification of Grid Communication Based on Coverage Range & Data Rate	12
2.8	Architecture of Grid Communication . . . . .	12
2.9	Domain of Smart Grid . . . . .	13
2.10	Standard of Grid Communication . . . . .	14
2.11	Traffic Queuing Classification Model Scheme . . . . .	19
2.12	Structure of ndnSIM . . . . .	20
2.13	NDN Packet Exchange Process in ndnSIM . . . . .	21
3.1	Scheme Data Flow I . . . . .	22
3.2	Scheme Data Flow II . . . . .	23
3.3	Network Topology . . . . .	26
3.4	Network Topology - 320 Node . . . . .	27
3.5	Network Topology - 640 Node . . . . .	27
4.1	Average Network Delay - System Models I . . . . .	36
4.2	Detailed Avg. Network Delay - System Models I . . . . .	37
4.3	Packet Hit Non Class . . . . .	38
4.4	Cache Hit Non Class . . . . .	38
4.5	Packet Drop in Node Utility - System Models I . . . . .	39
4.6	Network Packet Drop - System Models I . . . . .	39
4.7	Network Interest Timeout - System Models I . . . . .	40
4.8	Delay in Node 15 - System Models II . . . . .	40
4.9	Network Delay - System Models II . . . . .	41
4.10	Cache Hit Ratio in Intermediate Router . . . . .	42
4.11	Interest Request, Timeout & Packet Drop - System Models II . . . . .	43
4.12	Total Interest Request - 320 Metering Device . . . . .	44
4.13	Interest Timeout Ratio - 320 Metering . . . . .	44
4.14	Interest Request vs Timeout - 320 Metering . . . . .	45
4.15	Cache Hit Ratio - 320 Metering . . . . .	45

4.16 Average Delay - 320 Metering . . . . .	46
4.17 Packet Drop - 320 Metering . . . . .	47
4.18 Total Interest Request - 640 Metering . . . . .	47
4.19 Interest Request vs Timeout - 640 Metering . . . . .	48
4.20 Detail Interest Timeout - 640 Metering . . . . .	48
4.21 Average Delay - 640 Metering . . . . .	49
4.22 Cache Hit Ratio - 640 Metering . . . . .	49
4.23 Packet Drop - 640 Metering . . . . .	50