

DAFTAR PUSTAKA

- [1] A. Development Bank, “Asian Water Development Strengthening Water Security in ASIA and the Pasific,” 2016, Accessed: Jun. 06, 2023. [Online]. Available: www.adb.org
- [2] BPKB, “Laporan Kinerja 2017,” Feb. 2018.
- [3] X. J. Li and P. H. J. Chong, “Design and Implementation of a Self-Powered Smart Water Meter,” *Sensors*, vol. 19, no. 19, 2019, doi: 10.3390/s19194177.
- [4] Q. Zhang *et al.*, “Water meter pointer reading recognition method based on target-key point detection,” *Flow Measurement and Instrumentation*, vol. 81, p. 102012, 2021, doi: <https://doi.org/10.1016/j.flowmeasinst.2021.102012>.
- [5] “Utang Pelanggan PDAM Tirta Kelimutu Capai 7,2 Miliar Rupiah | BPK RI Perwakilan Propinsi Nusa Tenggara Timur.” Accessed: Jun. 06, 2023. [Online]. Available: <https://ntt.bpk.go.id/utang-pelanggan-pdam-tirta-kelimutu-capai-72-miliar-rupiah/>
- [6] Pusat Penelitian dan Pengembangan Pemukiman Balitbang Kementerian Pekerjaan Umum, “Spesifikasi Meter Air.” 2014.
- [7] Y. Li, X. Yan, L. Zeng, and H. Wu, “Research on water meter reading system based on LoRa communication,” in *2017 IEEE International Conference on Smart Grid and Smart Cities (ICSGSC)*, 2017, pp. 248–251. doi: 10.1109/ICSGSC.2017.8038585.
- [8] R. Muhendra, Husein, M. Budiman, and Khairurrijal, “Development of digital water meter infrastructure using wireless sensor networks,” *AIP Conf Proc*, vol. 1746, no. 1, p. 020025, Jun. 2016, doi: 10.1063/1.4953950.
- [9] T. Kot, “LC Sensor Rotation Detection With MSP430™ Extended Scan Interface (ESI) Application Report LC Sensor Rotation Detection With MSP430™ Extended Scan Interface (ESI),” 2014. Accessed: Jun. 07, 2023. [Online]. Available: www.ti.com
- [10] K. Technologies, “4 Tips to Optimize IoT Device Battery Life Battery Life Is IoT Device Life Four Tips to Optimize Battery Life in IoT Devices Contents.”
- [11] J. Xiong, M. F. Lin, J. Wang, S. L. Gaw, K. Parida, and P. S. Lee, “Wearable All-Fabric-Based Triboelectric Generator for Water Energy Harvesting,” *Adv Energy Mater*, vol. 7, no. 21, Nov. 2017, doi: 10.1002/aenm.201701243.
- [12] Viral Nagda, “Difference Between Solenoid Valve and Motorized Valve.” Accessed: Jun. 07, 2023. [Online]. Available: <https://instrumentationtools.com/difference-between-solenoid-valve-and-motorized-valve/>
- [13] A. Lombardo, S. Parrino, G. Peruzzi, and A. Pozzebon, “LoRaWAN Versus NB-IoT: Transmission Performance Analysis Within Critical Environments,” *IEEE Internet Things J*, vol. 9, no. 2, pp. 1068–1081, Jan. 2022, doi: 10.1109/JIOT.2021.3079567.

- [14] STMicroelectronics, “Demonstration of LC sensor for gas or water metering based on STM32L073Z-EVAL and STM32L476RG-NUCLEO boards.” Accessed: Dec. 29, 2023. [Online]. Available: www.st.com
- [15] LoRa Alliance Technical Committee, “LoRaWAN™ 1.0.3 Specification,” *LoRa™ Alliance*, 2018, Accessed: Jan. 08, 2024. [Online]. Available: <https://lora-alliance.org>
- [16] LoRa Alliance Technical Committee Regional Parameters Workgroup, “LoRaWAN 1.0.3 Regional Parameters,” 2018.
- [17] A. Pötsch and F. Haslhofer, “Practical limitations for deployment of LoRa gateways,” in *2017 IEEE International Workshop on Measurement and Networking (M&N)*, 2017, pp. 1–6. doi: 10.1109/IWMN.2017.8078360.
- [18] A. Lavric and V. Popa, “A LoRaWAN: Long range wide area networks study,” in *2017 International Conference on Electromechanical and Power Systems (SIELMEN)*, 2017, pp. 417–420. doi: 10.1109/SIELMEN.2017.8123360.
- [19] “Panasonic-Eneloop-BK-3MC-Datasheet”.
- [20] M. Swierczynski, D.-I. Stroe, A.-I. Stan, R. Teodorescu, and S. Knudsen Kaer, “Investigation on the Self-discharge of the LiFePO₄/C Nanophosphate Battery Chemistry at Different Conditions.”
- [21] L. Wuhan Voltec Energy Sources Co., “Sunmoon Battery ER26500 Datasheet”, Accessed: Jan. 18, 2024. [Online]. Available: www.voltec-sunmoon.com
- [22] S. Maheriya and P. Parikh, “A review: Modelling of Brushed DC motor and Various type of control methods,” *Journal for Research*, vol. 1, 2016.
- [23] Y. Luo, L. Pu, G. Wang, and Y. Zhao, “RF Energy Harvesting Wireless Communications: RF Environment, Device Hardware and Practical Issues,” *Sensors*, vol. 19, no. 13, 2019, doi: 10.3390/s19133010.
- [24] Y. Chapre, P. Mohapatra, S. Jha, and A. Seneviratne, “Received signal strength indicator and its analysis in a typical WLAN system (short paper),” in *38th Annual IEEE Conference on Local Computer Networks*, 2013, pp. 304–307. doi: 10.1109/LCN.2013.6761255.
- [25] K. Kaemarungsi and P. Krishnamurthy, “Analysis of WLAN’s received signal strength indication for indoor location fingerprinting,” *Pervasive Mob Comput*, vol. 8, no. 2, pp. 292–316, 2012, doi: <https://doi.org/10.1016/j.pmcj.2011.09.003>.
- [26] B. Debaillie *et al.*, “Analog/RF Solutions Enabling Compact Full-Duplex Radios,” *IEEE Journal on Selected Areas in Communications*, vol. 32, no. 9, pp. 1662–1673, 2014, doi: 10.1109/JSAC.2014.2330171.
- [27] F. Turcinovic, J. Vukovic, S. Božo, and G. Sisul, *Analysis of LoRa Parameters in Real-World Communication*. 2020. doi: 10.1109/ELMAR49956.2020.9219028.
- [28] A. Rahman and M. Suryanegara, “The development of IoT LoRa: A performance evaluation on LoS and Non-LoS environment at 915 MHz ISM frequency,” in

2017 International Conference on Signals and Systems (ICSigSys), 2017, pp. 163–167. doi: 10.1109/ICSIGSYS.2017.7967033.

- [29] O. Elijah, T. A. Rahman, Haziq. I. Saharuddin, and Fatin. N. Khairodin, “Factors that Impact LoRa IoT Communication Technology,” in *2019 IEEE 14th Malaysia International Conference on Communication (MICC)*, 2019, pp. 112–117. doi: 10.1109/MICC48337.2019.9037503.
- [30] H. M. Ramos *et al.*, “New Challenges towards Smart Systems’ Efficiency by Digital Twin in Water Distribution Networks,” *Water (Basel)*, vol. 14, no. 8, 2022, doi: 10.3390/w14081304.