REFERENCES

[1]   T. N. Trang Tran, M. Atas, A. Felfernig, and M. Stettinger, "An overview of recommender systems in the healthy food domain," *J Intell Inf Syst*, vol. 50, no. 3, pp. 501–526, Jun. 2018, doi: 10.1007/s10844-017-0469-0.

[2]   M. F. Mat Baseri and A. F. Saad, "Dietry Monitoring System Using Decision Tree to Control Human Obesity," *International Journal of Artificial Intelligence*, vol. 10, no. 1, pp. 9–20, Jun. 2023, doi: 10.36079/lamintang.ijai-01001.485.

[3]   I. Lovita, M. Hendrianingtyas, and R. Triwardhani, "Hubungan resting metabolic rate (RMR) dan komposisi tubuh dengan kadar HbA1c pada obesitas," *Intisari Sains Medis*, vol. 10, no. 1, Apr. 2019, doi: 10.15562/ism.v10i1.345.

[4]   M. Bastien, P. Poirier, I. Lemieux, and J.-P. Després, "Overview of Epidemiology and Contribution of Obesity to Cardiovascular Disease," *Progress in Cardiovascular Diseases*, vol. 56, no. 4, pp. 369–381, Jan. 2014, doi: 10.1016/j.pcad.2013.10.016.

[5]   I. E. Young, A. Poobalan, K. Steinbeck, H. T. O'Connor, and H. M. Parker, "Distribution of energy intake across the day and weight loss: A systematic review and meta‑analysis," *Obesity Reviews*, vol. 24, no. 3, p. e13537, Mar. 2023, doi: 10.1111/obr.13537.

[6]   P. J. Huth, V. L. Fulgoni, D. R. Keast, K. Park, and N. Auestad, "Major food sources of calories, added sugars, and saturated fat and their contribution to essential nutrient intakes in the U.S. diet: data from the national health and nutrition examination survey (2003–2006)," *Nutr J*, vol. 12, no. 1, p. 116, Dec. 2013, doi: 10.1186/1475-2891-12-116.

[7]   Z. Yuan and F. Luo, "Personalized Diet Recommendation Based on K-means and Collaborative Filtering Algorithm," *J. Phys.: Conf. Ser.*, vol. 1213, no. 3, p. 032013, Jun. 2019, doi: 10.1088/1742-6596/1213/3/032013.

[8]   E. E. M. Da Rocha, V. G. F. Alves, and R. B. V. Da Fonseca, "Indirect calorimetry: methodology, instruments and clinical application:," *Current Opinion in Clinical Nutrition and Metabolic Care*, vol. 9, no. 3, pp. 247–256, May 2006, doi: 10.1097/01.mco.0000222107.15548.f5.

[9]   D. Kotkov, J. A. Konstan, Q. Zhao, and J. Veijalainen, "Investigating serendipity in recommender systems based on real user feedback," in *Proceedings of the 33rd Annual ACM Symposium on Applied Computing*, Pau France: ACM, Apr. 2018, pp. 1341–1350. doi: 10.1145/3167132.3167276.

[10]   S. Fazeli, H. Drachsler, M. Bitter-Rijpkema, F. Brouns, W. V. D. V. Brouns, and P. B. Sloep, "User-Centric Evaluation of Recommender Systems in Social Learning Platforms: Accuracy is Just the Tip of the Iceberg," *IEEE Trans. Learning Technol.*, vol. 11, no. 3, pp. 294–306, Jul. 2018, doi: 10.1109/TLT.2017.2732349.

[11]   S. M. McNee, J. Riedl, and J. A. Konstan, "Making recommendations better: an analytic model for human-recommender interaction," in *CHI '06 Extended Abstracts on Human Factors in Computing Systems*, Montréal Québec Canada: ACM, Apr. 2006, pp. 1103–1108. doi: 10.1145/1125451.1125660.

[12]   G. Agapito *et al.*, "DIETOS: A dietary recommender system for chronic diseases monitoring and management," *Computer Methods and Programs in Biomedicine*, vol. 153, pp. 93–104, Jan. 2018, doi: 10.1016/j.cmpb.2017.10.014.

[13]   S. Hamdollahi Oskouei and M. Hashemzadeh, "FoodRecNet: a comprehensively personalized food recommender system using deep neural networks," *Knowl Inf Syst*, vol. 65, no. 9, pp. 3753–3775, Sep. 2023, doi: 10.1007/s10115-023-01897-4.

[14]   M. De Gemmis, P. Lops, G. Semeraro, and C. Musto, "An investigation on the serendipity problem in recommender systems," *Information Processing & Management*, vol. 51, no. 5, pp. 695–717, Sep. 2015, doi: 10.1016/j.ipm.2015.06.008.

[15]   D. Kotkov, A. Medlar, and D. Glowacka, "Rethinking Serendipity in Recommender Systems," in *Proceedings of the 2023 Conference on Human Information Interaction and Retrieval*, Austin TX USA: ACM, Mar. 2023, pp. 383–387. doi: 10.1145/3576840.3578310.

[16]   R. Hendrawan, Adiwijaya, and S. Al Faraby, "Multilabel Classification of Hate Speech and Abusive Words on Indonesian Twitter Social Media," in *2020 International Conference on Data Science and Its Applications (ICoDSA)*, Bandung, Indonesia: IEEE, Aug. 2020, pp. 1–7. doi: 10.1109/ICoDSA50139.2020.9212962.

[17]   Rianto, A. B. Mutiara, E. P. Wibowo, and P. I. Santosa, "Improving the accuracy of text classification using stemming method, a case of non-formal Indonesian conversation," *J Big Data*, vol. 8, no. 1, p. 26, Dec. 2021, doi: 10.1186/s40537-021-00413-1.

[18]   M. W. Putri, A. Muchayan, and M. Kamisutara, "Sistem Rekomendasi Produk Pena Eksklusif Menggunakan Metode Content-Based Filtering dan TF-IDF," *JOINTECS*, vol. 5, no. 3, p. 229, Sep. 2020, doi: 10.31328/jointecs.v5i3.1563.

[19]   S. Bandyopadhyay, S. S. Thakur, and J. K. Mandal, "Product recommendation for e-commerce business by applying principal component analysis (PCA) and K-means clustering: benefit for the society," *Innovations Syst Softw Eng*, vol. 17, no. 1, pp. 45–52, Mar. 2021, doi: 10.1007/s11334-020-00372-5.

[20]   H. Boone and D. Boone, "Analyzing Likert Data," *JOE*, vol. 50, no. 2, Apr. 2012, doi: 10.34068/joe.50.02.48.