

DAFTAR SINGKATAN

API	: <i>Application Programming Interface</i>
ARM	: <i>Advanced RISC Machine</i>
Bansos	: Bantuan Sosial
BULOG	: Badan Urusan Logistik
BUMN	: Badan Usaha Milik Negara
BW	: <i>Bandwidth</i>
Cm	: <i>centimeter</i>
CST	: <i>Computer Simulation Technology</i>
CTRL	: <i>Control</i>
dB	: Desibel
dB _i	: Desibel Isotropic
dB _m	: Desibel-miliwatts
DOM	: <i>Document Object Model</i>
EN	: <i>Enable</i>
FR-4	: <i>Flame Retardant – 4</i>
FSL	: <i>Free Space Loss</i>
GHz	: Gigahertz
GND	: <i>Ground</i>
GPIO	: <i>General Purpose Input Output</i>
HTML	: <i>Hypertext Markup Language</i>
HTTP	: <i>Hypertext Transfer Protocol</i>
IEEE	: <i>Institute of Electrical and Electronics Engineers</i>
IP	: <i>Internet Protocol</i>
IoT	: <i>Internet of Things</i>
I ² C	: <i>Inter Integrated Circuit</i>

LCD	: <i>Liquid Crystal Display</i>
OLED	: <i>Organic Light Emitting Diode</i>
MHz	: Megahertz
mm	: Milimeter
ms	: Milisekon
OS	: <i>Operating System</i>
PC	: <i>Personal Computer</i>
PDF	: <i>Portable Document Format</i>
PETG	: <i>Polyethylene Terephthalate Glycol</i>
QoS	: <i>Quality of Service</i>
RF	: <i>Radio Frequency</i>
RFDT	: <i>Radio Frequency Double Throw</i>
RL	: <i>Return Loss</i>
RMSE	: <i>Root Mean Square Error</i>
RMSE	: <i>Root Mean Square Error</i>
Rp	: Rupiah
SCL	: Serial Clock
SDA	: Serial Data
SNI	: Standar Nasional Indonesia
S-Parameter	: <i>Scattering Parameter</i>
TCP	: <i>Transmission Control Protocol</i>
UI	: <i>User Interface</i>
UID	: <i>Unique Identifier</i>
URL	: <i>Uniform Resource Locator</i>
USB	: <i>Universal Serial Bus</i>
VNA	: <i>Vector Network Analyzer</i>

VSWR : *Voltage Standing Wave Ratio*

WiFi : *Wireless Fidelity*

3D : 3 Dimensi