

## Referensi

- [1] I. Baidillah *et al.*, “Direktori Aksara Sunda untuk Unicode,” *Pemerintah Provinsi Jawa Barat Dinas Pendidikan. Provinsi Jawa Barat*, p. 131, 2008.
- [2] E. Granell, E. Chammas, L. Likforman-Sulem, C. D. Martínez-Hinarejos, C. Mokbel, and B. I. Cîrstea, “Transcription of Spanish historical handwritten documents with deep neural networks,” *J. Imaging*, vol. 4, no. 1, 2018, doi: 10.3390/jimaging4010015.
- [3] E. Paulus, S. Hadi, M. Suryani, I. Suryana, and Y. D. Simanjuntak, “Evaluating Ancient Sundanese Glyph Recognition Using Convolutional Neural Network,” *J. Phys. Conf. Ser.*, vol. 1235, no. 1, pp. 1–7, 2019, doi: 10.1088/1742-6596/1235/1/012063.
- [4] A. Barucci, C. Cucci, M. Franci, M. Loschiavo, and F. Argenti, “A Deep Learning Approach to Ancient Egyptian Hieroglyphs Classification,” *IEEE Access*, vol. 9, pp. 123438–123447, 2021, doi: 10.1109/ACCESS.2021.3110082.
- [5] D. Singh *et al.*, “DKNet: Deep Kuzushiji Characters Recognition Network,” *IEEE Access*, vol. 10, no. June, pp. 75872–75883, 2022, doi: 10.1109/ACCESS.2022.3191429.
- [6] A. A. Hidayat, K. Purwandari, T. W. Cenggoro, and B. Pardamean, “A Convolutional Neural Network-based Ancient Sundanese Character Classifier with Data Augmentation,” *Procedia Comput. Sci.*, vol. 179, no. 2020, pp. 195–201, 2021, doi: 10.1016/j.procs.2020.12.025.
- [7] M. Sandler, A. Howard, M. Zhu, and A. Zhmoginov, “MobileNetV2: Inverted Residuals and Linear Bottlenecks,” *arXiv*, pp. 4510–4520, 2018.
- [8] N. Syafi’al Arief, W. Anggara Putra, D. Septhian, and R. Pratama, “Implementasi Cnn Arsitektur Mobilenetv2 Untuk Klasifikasi Tulisan Aksara Jawa,” *Sainteks*, vol. 3, pp. 298–303, 2024.
- [9] T. S. Girsang, I. D. M. B. A. Darmawan, N. A. S. ER, A. A. I. N. E. Karyawati, I. P. G. H. Suputra, and C. R. A. Pramatha, “Pengembangan Sistem Pengenalan Karakter Aksara Suku Simalungun Berbasis Android,” *JELIKU (Jurnal Elektron. Ilmu Komput. Udayana)*, vol. 11, no. 3, p. 617, 2022, doi: 10.24843/jlk.2023.v11.i03.p18.
- [10] K. Dong, C. Zhou, Y. Ruan, and Y. Li, “MobileNetV2 Model for Image Classification,” *Proc. - 2020 2nd Int. Conf. Inf. Technol. Comput. Appl. ITCA 2020*, pp. 476–480, 2020, doi: 10.1109/ITCA52113.2020.00106.
- [11] L. Yong, L. Ma, D. Sun, and L. Du, “Application of MobileNetV2 to waste classification,” *PLoS One*, vol. 18, no. 3 March, pp. 1–16, 2023, doi: 10.1371/journal.pone.0282336.
- [12] A. Sobhy, M. Helmy, M. Khalil, S. Elmasry, Y. Boules, and N. Negied, “An AI Based Automatic Translator for Ancient Hieroglyphic Language - From Scanned Images to English Text,” *IEEE Access*, vol. 11, no. April, pp. 38796–38804, 2023, doi: 10.1109/ACCESS.2023.3267981.
- [13] L. Chen, B. Lyu, H. Tomiyama, and L. Meng, “A Method of Japanese Ancient Text Recognition by Deep Learning,” *Procedia Comput. Sci.*, vol. 174, pp. 276–279, 2020, doi: 10.1016/j.procs.2020.06.084.
- [14] A. Susanto, I. U. W. Mulyono, C. A. Sari, E. H. Rachmawanto, D. R. I. M. Setiadi, and M. K. Sarker, “Handwritten Javanese script recognition method based 12-layers deep convolutional neural network and data augmentation,” *IAES Int. J. Artif. Intell.*, vol. 12, no. 3, pp. 1448–1458, 2023, doi: 10.11591/ijai.v12.i3.pp1448-1458.
- [15] D. Arifadilah, Asriyanik, and A. Pambudi, “Sunda Script Detection Using You Only Look Once Algorithm,” *J. Artif. Intell. Eng. Appl.*, vol. 3, no. 2, pp. 606–613, 2024, doi: 10.59934/jaiea.v3i2.443.
- [16] S. Ioffe and C. Szegedy, “Batch normalization: Accelerating deep network training by reducing internal covariate shift,” *32nd Int. Conf. Mach. Learn. ICML 2015*, vol. 1, pp. 448–456, 2015.
- [17] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, “Dropout: A simple way to prevent neural networks from overfitting,” *J. Mach. Learn. Res.*, vol. 15, pp. 1929–1958, 2014.
- [18] C. Cortes, G. Research, and N. York, “L2 Regularization for Learning Kernels,” *Proc. Twenty-Fifth Conf. Uncertain. Artif. Intell.*, pp. 109–116, 2004.